

> Universal Chargers

These can recharge many types of batteries and are perfect for high battery usage households. They are reliable and safe and can even test your batteries to see if its time for a recharge.

BC-0906S

BC-0906SMT

Charges:

1-4 x AA

1-4 x AAA

1-4 x D or C

1-2 x 9V



Ni-MH
Ni-Cd



SPECIFICATIONS

BC-0906S

Input: AC 110-120V ~ 60Hz or
220-240 ~ 50Hz

Output: DC 4x (1.4V \approx 250mA) D/C/AA/
AAA Size
2x (9V \approx 25mA) 9V Size

BC-0906SMT

Input: AC 100-240V ~ 50/60Hz
Output: DC 4x (1.4V \approx 360mA) D/C/AA/
AAA Size
2x (9V \approx 25mA) 9V Size

MAIN FEATURES

BC-0906S

- 6 Independent Charging Channels
- Reverse Polarity Protection
- LED Indicators

Red	Charging or charge complete
-----	-----------------------------

BC-0906SMT

- 6 Independent Charging Channels
- 4 Selective Timer Control for different capacity batteries
- Reverse Polarity Protection
- Trickle Charge after auto cut-Off
- Built-in Switching Adaptor for worldwide use
- Built in Battery Discharger and Tester
- LED Indicators

Red	Charging
Red	Battery fully charged (9V battery only)
Off	Fully charged (for AAA/AA/C/D batteries)

CHARGING TIMES

Type of Battery	Charging Times (Appr.)	
	BC-0906S	BC-0688SMT
Ni-MH AA 2500mAh	11.0 h	7.7 h
Ni-MH AA 2000mAh	9.6 h	6.6 h
Ni-MH AA 1500mAh	7.0 h	5.0 h
Ni-MH AAA 600mAh	3.0 h	2.0 h
Ni-Cd AA 1000mAh	4.8 h	3.3 h
Ni-Cd AAA 300mAh	1.5 h	1.0 h
Ni-MH C 1800mAh	9.0 h	6.0 h
Ni-MH D 2500mAh	12.0 h	8.3 h
Ni-MH 9V 200 mAh	10.0 h	10.0 h

AVAILABLE COLORS

Grey Silver

PACKAGING



Blister		
Plug:	TUV	UL
Weight(g)	630	610
Dimensions (W) x (H) x (D) (mm)	250 x 155 x 85	250 x 155 x 85
Inner Carton		
Packs / Inner ctn	8	8
Net Weight(kg)	5.04	4.9
Gross Weight(kg)	5.56	5.42
Dimensions (L)x (W) x (H) (cm)	51.5 x 32.5 x 19	51.5 x 32.5 x 19
Outer Carton		
Packs / Carton	16	16
Net Weight(kg)	10.1	9.8
Gross Weight(kg)	12.3	12
Dimensions (L)x (W) x (H) (cm)	53 x 34 x 40.5	53 x 34 x 40.5
Volume(cbm)	0.0730	0.0730