- Conduit systems and accessories

- ▼ 50/52 Range Accessories for system assembly
 - ▼ Plastic cable glands for ATEX environments Zone 1(G) Zone 20 (D)
 - Plastic cable glands

ATEX polymer cable glands, PG-pitch - Grey RAL 7035 - IP68



Gewiss Code	Type of pitch	Mounting hole \emptyset (mm)	For cables Ø (mm)	Pack/Carton Qty.
<u>GW52101</u>	PG7	12.5	from 3 to 6.5	50/900
<u>GW52102</u>	PG9	16	from 4 to 8	50/600
<u>GW52103</u>	PG11	19	from 5 to 10	25/500
<u>GW52104</u>	PG13.5	20	from 6.5 to 12	25/500
<u>GW52105</u>	PG16	23	from 7 to 12	25/375
<u>GW52106</u>	PG21	29	from 13 to 18	25/400
<u>GW52107</u>	PG29	37	from 18 to 25	25/250
<u>GW52108</u>	PG36	48	from 22 to 32	10/130
<u>GW52109</u>	PG42	54	from 32 to 38	6/120
GW52110	PG48	60	from 37 to 44	5/100

ATEX VERSIONS CLASSIFICATION: 2G 1D Ex E -20°< Ta <+95°C

ATEX polymer cable glands, metric pitch - Grey RAL 7035 - IP68



Gewiss Code	Tymo	Mounting	For cables	Pack/Carton Qty.
Gewiss Code	Type of pitch	hole Ø (mm)	Ø (mm)	Fack/Carton Qty.
<u>GW52121</u>	M12	12	from 3 to 3.5	50/600
<u>GW52122</u>	M16	16	from 5 to 10	50/400
<u>GW52123</u>	M20	20	from 10 to 14	25/300
<u>GW52124</u>	M25	25	from 13 to 18	25/200
<u>GW52125</u>	M32	32	from 18 to 25	25/150
<u>GW52126</u>	M40	40	from 22 to 32	10/120
<u>GW52127</u>	M50	50	from 32 to 38	6/84
GW52128	M63	63	from 37 to 44	5/60

ATEX VERSIONS CLASSIFICATION: 2G 1D Ex E -20° < Ta < +95°C