



4 channels THERMOMETER

Model : TM-946

- * Type K/J, Pt 100 ohm, 4 display.
- * 4 channels (T1, T2, T3, T4), T1-T2, °C/°F.
- * Display 4 channels Temp. at the same time.
- * Type K : -100 to 1300 °C.
- * Type J : -100 to 1200 °C.
- * Pt 100 ohm : -199 to 850 °C.
- * °C/°F, 0.1 degree/1 degree.
- * Data hold, Record (max., min.).
- * RS-232/USB computer interface, data logger.
- * Optional Type K Temp. probe, refer page 47.
- * Optional Pt-100 ohm Temp. probe, TP-101.
- * DC 1.5V (UM-4, AAA) battery x 6 or DC 9V adapter in.



THERMOMETER, Type K/J/R/E/T

Model : TM-9126

- * Type K : -50 to 1300 °C, 0.1 °C/0.1 °F.
- * Type J : -50 to 1150 °C, 0.1 °C/0.1 °F.
- * Type T : -50 to 400 °C, 0.1 °C/0.1 °F.
- * Type E : -50 to 900 °C, 0.1 °C/0.1 °F.
- * Type R : 0 to 600 °C, 1 °C/1 °F.
- * Professional thermometer with multi-function.
- * Optional full range temperature probe.
- * RS-232/USB computer interface.
- * Data hold, Record (Max., Min.).
- * DC 1.5V (UM-4, AAA) battery x 6 or DC 9V adapter in.

Multi-function THERMOMETER, Real time data logger

Model : YK-2005TM

- * High capacity, 16,000 data logger point.
- * Real time data logger (record year, month, date, hour, minute, second).
- * Multi-function : Type K, Type J, Pt100 ohm, Infrared Thermometer.
- * Type K : -50 to 1300 °C, Type J : -100 to 1100 °C, Pt 100 ohm -200 to 850 °C.
- * Optional probe : Type K probe, Type J probe,, PT 100 probe, IR probe.
- * Max., Min., Data hold, zero adjust.
- * RS-232/USB computer interface.
- * Jumbo LCD display.
- * DC 1.5V (UM3, AA) x 4 PCs or DC 9V adapter in.
- * Size : 203 x 76 x 38 mm.



THERMOMETER, all in 1

Model : PTM-816

- * Cooperate with the type K Temp. probe.
- * Range : -50 to 230 °C x 0.1 °C.
- * Unit : °C, °F. internal adjustment.
- * Meter with the probe, all in 1, easy operation.
- * Hold function to freeze display value.
- * Build in reverse display button.
- * IP-67 Water resistance, heavy duty.
- * DC 1.5V battery (UM-4, AAA) x 4.

Separate probe, type K THERMOMETER

Model : PTM-806

- * Cooperate with the type K Temp. probe.
- * Range : -100 to 1300 °C x 0.1 °C.
- * Unit : °C, °F. internal adjustment.
- * Separate probe, easy for remoting measurement.
- * Temp. probe, TP-01 is included.
- * Optional temp. probe : TP-02A, TP-03, TP-04.
- * Hold function to freeze display value.
- * Build in reverse display button.
- * DC 1.5V battery (UM-4, AAA) x 4.



T1, T2, T1-T2, two displays

TWO CHANNEL THERMOMETER

Model : TM-925

- * T1, T2, T1-T2, Type K/J.
- * °C/°F, 0.1 degree/1 degree.
- * Type K : -100 to 1300 °C.
- * Type J : -100 to 1200 °C.
- * Data hold, Record (max., min.).
- * 1600 Data logger point.
- * RS-232/USB interface, data logger.
- * DC 9V battery (006P) or DC 9V adapter in.

