



H Standard extruded heatsinks

B

C

D

<b>art. no.</b>		
<b>SK 507 ...</b>		
<p>please indicate: ... <math>\longleftrightarrow</math> <b>37.5 50 75 100 1000 mm</b> ... <math>\diamond</math> (optional) <b>SSR 1; SSR 2</b></p>		

E

F

<b>art. no.</b>		
<b>SK 408 ...</b>		
<p>please indicate: ... <math>\longleftrightarrow</math> <b>50 75 100 150 1000 mm</b></p>		

G

H

<b>art. no.</b>		
<b>SK 546 ...</b>		
<p>please indicate: ... <math>\longleftrightarrow</math> <b>37.5 50 75 100 150 1000 mm</b></p>		

I

K

<b>art. no.</b>		
<b>SK 81 ...</b>		
<p>please indicate: ... <math>\longleftrightarrow</math> <b>37.5 50 75 100 1000 mm</b></p>		

M

N

A 41

H High decorative surfaces → A 9  
 Order example → A 21  
 Drilling pattern for Solid State Relays → A 12  
 Heatsink as visual & decor-parts → A 10

Heatsinks for Solid State Relay → A 11 - 12 H  
 Heatsink special design → A 133 - 134  
 Special profiles → A 136  
 Technical introduction → A 2 - 7