



WEBSITE PHOTOS

⚠ This dwg is for reference only, Actual dwg should be based on formal engineering dwg issued by Kang Yang.



A	B	C
10.0	3.5	6.3


 康揚企業股份有限公司  
 KANG YANG HARDWARE ENTERPRISE CO., LTD.  
 康揚塑膠(東莞)有限公司  
 KANG YANG PLASTIC(DONG GUAN) CO., LTD.  
 康哲電腦配件(吳江)有限公司  
 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.  
ISO 9001  
ISO 14001  
QC 080000

PART NUMBER		3.5-10	SPEC. DWG.	
TITLE				
ROUND SPACER				
MATERIAL			COLOR	
NYLON 66(UL) 94V-0			BLACK	
SIZE	SCALE	UNIT	CHECK	
A4	2:1	mm	Z.C	

PART NO	A	B	C	
3.5-1.6	1.6	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-2	2.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-3	3.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-3.5	3.5	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-4	4.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-4.5	4.5	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-5	5.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-6	6.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-7	7.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-7.5	7.5	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-8	8.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-9	9.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-9.5	9.5	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.
3.5-11	11.0	3.5	6.3	[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.



PART NO	A	B	C
3.5-12	12.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-13	13.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-14	14.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-15	15.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-15.5	15.5	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-16	16.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-17	17.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-17.7	17.7	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-18	18.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-19	19.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-20	20.0	3.5	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-21	21.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-22	22.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-23	23.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			



PART NO	A	B	C
3.5-24	24.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-25	25.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-26	26.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-27	27.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-28	28.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-28.5	28.57	3.55	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-29	29.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-30	30.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			
3.5-35	35.0	3.7	6.3
[1] NYLON 66(UL), Flame class: 94V-0/94V-2, Color: BLACK/NATURAL.			

