

# Black Body, Power Adapter Interface Cable, Test Lead Alligator clips

SERIES



## BLACK BODY

### Model : BB-400

- \* Black body, calibrator for the infrared thermometer.
- \* Temp. setting range : 33 °C ( room Temp. ) to 400 °C.
- \* Temp. setting resolution : 0.1 °C.
- \* Accuracy :  $\pm$  ( 1% + 1 °C ).
- \* Emissivity : 0.94.
- \* Sensing size : round, 120 mm dia.
- \* Power supply : 110 ACV or 220 ACV.
- \* Weight : approx. 12 Kg .
- \* Dimension ( HWD ) : 190 x 400 x 335 mm.



AP-9VA



AP-9VB



AP-GTU



AP-GTE

## DC 9V POWER ADAPTER

### Model : AP-9VA

- \* Input voltage : 100 to 240 ACV, 50/60 Hz.
- \* Output voltage : Regulation DC 9V/1 Amp. rating max.
- \* Output plug : round 2.5 mm dia. plug.

## DC 9V POWER ADAPTER

### Model : AP-9VB

- \* Input voltage : 100 to 240 ACV, 50/60 Hz.
- \* Output voltage : Regulation DC 9V/1 Amp. rating max.
- \* Output plug : 006p battery snap.

## PLUG CONVERTER

### Model : AP-GTU

- \* Convert the input plug of AP-9VA, AP-9VB from the Germany type to USA type.

## PLUG CONVERTER

### Model : AP-GTE

- \* Convert the input plug of AP-9VA, AP-9VB from the Germany type to UK ( England ) type.



USB-01



UPCB-01



UPCB-02



AL-05

## HEAVY DUTY ALLIGATORS

### Model : AL-05

- \* Heavy duty alligators.
- \* CATII-1000V approval, black & red suitable for banana plug and wire direct connection.

## HEAVY DUTY TEST LEAD

### Model : TL-88

- \* CATIII-1000V approval.
- \* High quality test lead with silicon rubber.

## RS232 CABLE

### Model : USB-01

- \* The computer interface cable, one side is the ear phone plug that connect to the meter's RS232 output, the other side is the USB plug that to connect the computer's USB terminal.
- \* Ship along with the driver software.

- \* Available for all the LUTRON instruments ( build in the RS232 interface ) , then the meter will have the USB interface.

## RS232 CABLE

### Model : UPCB-01, UPCB-02

- \* The computer interface cable, one side is the ear phone plug that connect to the meter's RS232 output, the other side is the D9 plug that to connect the computer's COM terminal.
- \* UPCB-01 is the direct interface cable.

- \* UPCB-02 is the isolated ( photo couple ) interface cable.
- \* Available for all the LUTRON instruments ( build in the RS232 interface )