



Chinland Solar Energy Co., Ltd.

合肥中南光电有限公司

Address: Feidong New City Economic Development Zone, Hefei, 231600,
Anhui Province, PR China Tel/Fax: +86 551 7759376/7758555
Web: www.chnland.com E-mail: sabrina.energy@gmail.com

Model :	
Monocrystalline silicon solar panel	CHN10-36M
Specification:	
Cell	Monocrystalline silicon solar cells 62.5*25mm
No. of cells and connections	36(4*9)
Solar Cell Efficiency	18.31%
Dimension of module (mm)	290*290*17
Limits	
Operating temperature	-40 to+85°C
Maximum system voltage	715 V DC
Temperature and Coefficients	
Nominal Operation Cell Temperature	48°C±2°C
Current temperature coefficient (%/k)	0.06±0.01
Voltage temperature coefficient (mV/k)	-(155±10)
Power temperature coefficient (%/k)	-(0.5±0.05)
Characteristics	
Model	CHN10-36M
Solar Panel Efficiency	11.89%
Tolerance	±5%
Open circuit voltage (Voc)	22.35V
Optimum operating voltage (Vmp)	18.1V
Short circuit Current (Isc)	0.59A
Optimum operating current (Imp)	0.55A
Maximum power at STC (Pm)	10Wp

Note: Test condition are STC Irradiance 1000W/m² with AM 1.5 spectrum, cell temperature 25°C, Test method according to IEC 904-1, Tolerance Efficiency 5% rel.

* These columns list typical value of production performance. Just for reference.