

尼龙绝缘护套公插端子(加铜套)(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡

**Nylon-Insulated Male Terminal (Double Copper Sleeve)**  
(Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin




### MALE TERMINAL

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color
					W	Dφ	dφ	L	H	
MDDN 1.25-110 D(5)	0.5-1.5 (22-16)	10A	0.5×2.8	0.5	2.8	3.8	1.7	17.7	11.0	红 red
MDDN 1.25-110 D(8)			0.8×2.8	0.8	2.8	3.8	1.7	17.7		
MDDN 1.25-187 D(5)			0.5×4.75	0.5	4.75	3.8	1.7	21.0		
MDDN 1.25-187 D(8)			0.8×4.75	0.8	4.75	3.8	1.7	21.0		
MDDN 1.25-250 D			0.8×6.35	0.4×2	6.35	3.8	1.7	21.0		

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color
					W	Dφ	dφ	L	H	
MDDN 2-187 D(5)	1.5-2.5 (16-14)	15A	0.5×4.75	0.5	4.75	4.4	2.3	21.0	11.0	蓝 blue
MDDN 2-187 D(8)			0.8×4.75	0.8	4.75	4.4	2.3	21.0		
MDDN 2-250 D			0.8×6.35	0.4×2	6.35	4.4	2.3	22.0		

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)					颜色 Color
					W	Dφ	dφ	L	H	
MDDN 5.5-250 D	4-6 (12-10)	24A	0.8×6.35	0.4×2	6.35	5.7	3.4	25.0	14.0	黄 yellow



PVC全绝缘护套母插端子(适用于软线)

- 材质: 黄铜
- 护套: PVC
- 表面处理: 镀锡

**Vinyl-Fully Insulated Female Terminal**  
(Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Vinyl
- Plating: Tin



### FEMALE TERMINAL

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)				颜色 Color
					W	Dφ	dφ	L	
FDFD 1.25-187(5)	0.5-1.5 (22-16)	10A	0.5×4.75	0.4	5.0	3.7	1.7	20.0	红 red
FDFD 1.25-187(8)			0.8×4.75		5.0	3.7	1.7	20.0	
FDFD 1.25-250			0.8×6.35		6.6	3.7	1.7	22.5	

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)				颜色 Color
					W	Dφ	dφ	L	
FDFD 2-187(5)	1.5-2.5 (16-14)	15A	0.5×4.75	0.4	5.0	4.1	2.3	20.0	蓝 blue
FDFD 2-187(8)			0.8×4.75		5.0	4.1	2.3	20.0	
FDFD 2-250			0.8×6.35		6.6	4.1	2.3	23.5	

型号 Item NO	导线截面mm <sup>2</sup> Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)				颜色 Color
					W	Dφ	dφ	L	
FDFD 5.5-250	4-6 (12-10)	24A	0.8×6.35	0.4	6.6	5.4	3.4	24.0	黄 yellow