


尼龙全绝缘护套母插端子(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡

Nylon-Fully Insulated Female Terminal
(Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin



尼龙全绝缘护套公插端子(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡

Nylon-Fully Insulating Male Terminal
(Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin



FEMALE TERMINAL

型号 Item NO	导线截面mm² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	F	L	B	Dφ	dφ	
FDFN 1.25-110(5)	0.5-1.5 (22-16)	10A	0.5×2.8	0.3	3.2	6.4	20.4	11.0	4.4	1.7	红 red
FDFN 1.25-110(8)			0.8×2.8		3.2	6.4	20.4	11.0	4.4		
FDFN 1.25-187(5)			0.5×4.75	0.4	5.0	6.4	21.4	10.5	3.5		
FDFN 1.25-187(8)			0.8×4.75		5.0	6.4	21.4	10.5	3.5		
FDFN 1.25-250			0.8×6.35		6.6	7.3	22.0	11.0	4.5		

型号 Item NO	导线截面mm² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	F	L	B	Dφ	dφ	
FDFN 2-110(5)	1.5-2.5 (16-14)	15A	0.5×2.8	0.3	3.2	6.4	20.4	11.0	4.5	2.3	蓝 blue
FDFN 2-110(8)			0.8×2.8		3.2	6.4	20.4	11.0	4.5		
FDFN 2-187(5)			0.5×4.75	0.4	5.0	6.4	20.4	11.0	4.2		
FDFN 2-187(8)			0.8×4.75		5.0	6.4	21.0	10.5	4.2		
FDFN 2-250			0.8×6.35		6.6	7.3	22.4	11.5	4.8		

型号 Item NO	导线截面mm² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	F	L	B	Dφ	dφ	
FDFN 5.5-250	4-6 (12-10)	24A	0.8×6.35	0.4	6.6	7.6	24.2	13.0	6.6	3.4	黄 yellow

MALE TERMINAL

型号 Item NO	导线截面mm² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	F	L	B	Dφ	dφ	
MDFN 1.25-250	0.5-1.5 (22-16)	10A	0.8×6.35	0.4×2	6.35	8.0	24.0	11.5	4.5	1.7	红 red

型号 Item NO	导线截面mm² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	F	L	B	Dφ	dφ	
MDFN 2-250	1.5-2.5 (16-14)	15A	0.8×6.35	0.4×2	6.35	8.0	24.3	11.3	4.5	2.3	蓝 blue

型号 Item NO	导线截面mm² Cable Size A.W.G	最大电流 Max Current	接插规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color
					W	F	L	B	Dφ	dφ	
MDFN 5.5-250	4-6 (12-10)	24A	0.8×6.35	0.4×2	6.35	8.0	25.5	14.0	6.5	3.4	黄 yellow