



HOME

ABOUT US

PRODUCTS

NEWS

LOCATION


CONTACT

中文版

PRODUCTS

- MKP(X2)
- MAC(CBB61)
- MEF(CL21)
- MET(CL20)
- MEA(CL20)
- MEC(CL23)
- MEM(CL21X)
- MPP(CBB21)
- MPT(CBB20)
- MPA(CBB20)
- MPC(CBB23)
- PEI(CL11)
- PEN(CL12)
- PPN(CBB13)
- PPS(CBB81)
- **MEB(CL23X)**
- MXY
- RC

ISO 9001
ISO 14001

PRODUCTS**MEB(CL23X)****FEATURES:**

- ★ Small size can be compacted favourably with the stacked film capacitors
- ★ Low loss and good stability
- ★ Long life due to excellent self-healing

APPLICATIONS:


- ★ Widely used in coupling, filter, noise-suppression by-passing of DC and pulse circuits in all kinds of machines

SPECIFICATIONS:

- ※DIELECTRIC: Polyester film
- ※ELECTRODES: Vacuum evaporated metal
- ※COATING: Encapsulated in reinforced flame retardant plastic case sealed with epoxy resin meeting the requirement of UL94V-0
- ※LEADS: Radial leads of tinned wire
- ※REFERENCE
- STANDARD : GB7322;IEC60384-2
- ※CLIMATIC
- CATALOGUE: 40/85/21(From 85°C up to 105°C with derating voltage 1.25%/°C)
- ※CAPACITANCE VERSUS RATED VOLTAGE (UR):
0.001uF-1.0uF/50V/63V 0.00uF-0.68uF/100VDC
0.001uF-0.15uF/250VDC;
- ※CAPACITANCE TOLERANCE: M=±20% K=±10% J=±5%
- ※DISSIPATION FACTOR
(TANGENT OF LOSS): DF≤1.0%(at 20°C, 1KHz)
- ※VOLTAGE PROOF: 1.6*Ur(5S at 20°C)
- ※INSULATION RESISTANCE: C≤0.33uF IR≥15000MΩ;
C>0.33uF IR*C≥3000S
Ur≤100V Testing by 50V
Ur>100V Testing by 100V
(1 minute at 20°C and RH≤65%)
- ※ENDURANCE: 1000hours with 125% of rated voltage at 85°C.
- After the test:
ΔC/C≤5%; ΔDF≤0.20%;
C≤0.1uF IR≥9000MΩ C>1 uF
IR≥50% of the specified value(20°C 1KHz)

★OUTLINE DRAWING 外观图

★ PICTURE 实物图



★DIMENSIONS 尺寸

UNIT 单位:mm

capacitance	nF	50/63VDC					100VDC					250VDC				
		W	H	T	P	dφ	W	H	T	P	dφ	W	H	T	P	dφ
102	0.0010	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
122	0.0012	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
152	0.0015	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
182	0.0018	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
222	0.0022	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
272	0.0027	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
332	0.0033	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
392	0.0039	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
472	0.0047	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
562	0.0056	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
682	0.0068	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
822	0.0082	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
103	0.010	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
123	0.012	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
153	0.015	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
183	0.018	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5
223	0.022	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	7.5	3.5	5.0	0.5
273	0.027	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	7.5	3.5	5.0	0.5
333	0.033	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	7.5	3.5	5.0	0.5
393	0.039	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	7.5	3.5	5.0	0.5
473	0.047	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	9.5	4.5	5.0	0.6
563	0.056	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	9.5	4.5	5.0	0.6
683	0.068	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	9.5	4.5	5.0	0.6
823	0.082	7.2	6.5	2.5	5.0	0.5	7.2	6.5	2.5	5.0	0.5	7.2	10.0	5.0	5.0	0.6
104	0.10	7.2	6.5	2.5	5.0	0.5	7.2	7.5	3.5	5.0	0.5	7.2	10.0	5.0	5.0	0.6
124	0.12	7.2	6.5	2.5	5.0	0.5	7.2	9.5	4.5	5.0	0.6	7.2	11.0	6.0	5.0	0.6
154	0.15	7.2	7.5	3.5	5.0	0.5	7.2	9.5	4.5	5.0	0.6	7.2	11.0	6.0	5.0	0.6
184	0.18	7.2	7.5	3.5	5.0	0.5	7.2	9.5	4.5	5.0	0.6					
224	0.22	7.2	7.5	3.5	5.0	0.5	7.2	10.0	5.0	5.0	0.6					
274	0.27	7.2	9.5	4.5	5.0	0.6	7.2	10.0	5.0	5.0	0.6					
334	0.33	7.2	9.5	4.5	5.0	0.6	7.2	11.0	6.0	5.0	0.6					
394	0.39	7.2	9.5	4.5	5.0	0.6	7.2	11.0	6.0	5.0	0.6					
474	0.47	7.2	10.0	5.0	5.0	0.6	7.2	11.0	6.0	5.0	0.6					
564	0.56	7.5	10.0	5.0	5.0	0.6	7.5	11.0	6.0	5.0	0.6					
684	0.68	7.2	11.0	6.0	5.0	0.6	7.2	11.0	6.0	5.0	0.6					
824	0.82	7.2	11.0	6.0	5.0	0.6										
105	1.0	7.2	11.0	6.0	5.0	0.6										

SPECIAL SIZE OR ITEMS ON REQUEST)可依需求制作特殊规格

[CLOSE]