


PVC绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Ring Terminal
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin



PVC绝缘护套圆形端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Ring Terminal
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin



RING TERMINAL

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color
						W	L	F	E	DΦ	dΦ	
RV0.5-3	0.2-0.75 (24-18)	0.5	10A	#4	3.2	5.7	18.3	5.4	10.0	2.7	1.3	黄 yellow
RV0.5-3.5S				#6	3.7	5.7	18.3	5.4				
RV0.5-3.5M				#6	3.7	6.6	19.9	6.3				
RV0.5-4				#8	4.3	6.6	19.9	6.3				

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color
						W	L	F	E	DΦ	dΦ	
RV 1.25-3	0.5-1.5 (22-16)	0.75	19A	#4	3.2	5.7	17.8	4.9	10.7	4.2	1.7	红 red
RV 1.25-3.5S				#6	3.7	5.7	17.8	4.9				
RV 1.25-3.5M				#6	3.7	6.6	20.1	6.3				
RV 1.25-3.5L				#6	3.7	8.0	21.5	7.6				
RV 1.25-4S				#8	4.3	6.6	20.1	6.3				
RV 1.25-4L				#8	4.3	8.0	21.5	7.0				
RV 1.25-5S				#10	5.3	8.0	21.5	7.0				
RV 1.25-5L				#10	5.3	9.8	23.0	7.6				
RV 1.25-6S				1/4	6.4	9.8	23.0	7.6				
RV 1.25-6L				1/4	6.4	11.6	27.5	11.1				
RV 1.25-8				5/16	8.4	11.6	27.5	11.1				
RV 1.25-10				3/8	10.5	13.6	31.6	13.9				
RV 1.25-12	1/2	13.0	19.2	36.0	16.5							

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color
						W	L	F	E	DΦ	dΦ	
RV 2-3	1.5-2.5 (16-14)	0.8	27A	#4	3.2	6.6	18.5	4.3	10.7	4.9	2.3	蓝 blue
RV 2-3.5S				#6	3.7	6.6	18.5	4.7				
RV 2-3.5M				#6	3.7	6.6	20.0	6.0				
RV 2-3.5L				#6	3.7	8.5	22.5	7.7				
RV 2-4S				#8	4.3	6.6	20.0	6.5				
RV 2-4L				#8	4.3	8.5	22.5	7.7				
RV 2-5S				#10	5.3	8.5	22.5	7.7				
RV 2-5L				#10	5.3	9.5	22.5	7.0				
RV 2-6S				1/4	6.4	9.5	22.5	7.0				
RV 2-6L				1/4	6.4	12.0	27.6	11.0				
RV 2-8				5/16	8.4	12.0	27.6	11.0				
RV 2-10				3/8	10.5	14.6	31.2	13.0				
RV 2-12	1/2	13.0	19.2	35.7	15.5							

RING TERMINAL

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color
						W	L	F	E	DΦ	dΦ	
RV 3.5-4	2.5-4 (14-12)	1.0	37A	#8	4.3	8.0	25.3	7.7	13.8	5.8	3.0	黑 black
RV 3.5-5S				#10	5.3	8.0	25.3	7.7				
RV 3.5-5L				#10	5.3	12.0	27.9	9.3				
RV 3.5-6				1/4	6.4	12.0	29.0	9.3				
RV 3.5-8				5/16	8.4	15.0	35.0	14				
RV 3.5-10				3/8	10.5	15.0	34.6	14				

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color
						W	L	F	E	DΦ	dΦ	
RV 5.5-3	4-6 (12-10)	1.0	48A	#4	3.2	7.2	22.7	6.1	14.0	6.3	3.4	黄 yellow
RV 5.5-3.5				#6	3.7	7.2	22.7	5.9				
RV 5.5-4S				#8	4.3	7.2	22.7	5.9				
RV 5.5-4L				#8	4.3	9.5	26.3	8.3				
RV 5.5-5				#10	5.3	9.5	26.3	8.3				
RV 5.5-6				1/4	6.4	12.0	30.0	11.0				
RV 5.5-8				5/16	8.4	15.0	34.7	13.7				
RV 5.5-10				3/8	10.5	15.0	34.7	13.7				
RV 5.5-12				1/2	13.0	19.2	39.0	16.0				

型号 Item NO	导线截面mm² Cable Size A.W.G	材料厚度 Thickness (mm)	最大电流 Max Current	美制螺栓号 USA Screw	螺栓口直径 Screw Dia. d2(mm)	尺寸Dimension(mm)						颜色 Color
						W	L	F	E	DΦ	dΦ	
RV 8-4	6.0-10 (8)	1.2	62A	#8	4.3	8.8	32.3	11.0	17.0	8.0	4.5	红 red
RV 8-5S				#10	5.3	8.8	32.3	13.3				
RV 8-5M				#10	5.3	12.0	32.3	9.3				
RV 8-5L				#10	5.3	15.0	38.3	13.8				
RV 8-6S				1/4	6.4	12.0	32.3	9.8				
RV 8-6L				1/4	6.4	15.0	38.3	13.8				
RV 8-8				5/16	8.4	15.0	38.3	13.8				
RV 8-10				3/8	10.5	15.0	38.3	13.8				
RV 8-12				1/2	13.0	22.0	48.0	20.5				