

Conductivity SERIES

CD



CONDUCTIVITY METER

Model : YK-43CD

- * 2 Ranges : 2 mS, 20 mS.
- * Large LCD display, 21.5 mm digit height.
- * Automatic temperature compensation.
- * Data hold, professional housing case.



CONDUCTIVITY METER

Model : CD-4303

- * μ -P circuit, LCD with display unit.
- * Max., Min., Memory recall button.
- * 200 μ S/2 mS/20 mS, ATC, Cell Adj.
- * RS232/USB computer interface.
- * Size : 180 x 72 x 32 mm .



CONDUCTIVITY METER

Model : CD-4303HA

- * μ -P circuit, LCD with display unit.
- * Max., Min., Memory recall button.
- * 200 μ S/2mS/20mS, ATC, Cell adj.
- * Size : 185 x 78 x 38 mm.



CONDUCTIVITY METER, Real time data logger

Model : YK-2005CD

- * High capacity, 16,000 data logger no.
- * Real time data logger (record year, month, date, hour, minute, second).
- * Range : 200 μ S/2 mS/20 mS/200 mS.
- * Automatic temp. compensation, ATC factor adj.
- * Carbon rod electrode for long life.
- * Max., Min., Data hold, zero adjust.
- * RS232/USB computer interface.
- * Jumbo LCD display.
- * DC 1.5V (UM3, AA) x 4 PCs or DC 9V adapter in.
- * Size : 203 x 76 x 38 mm.



CD + TDS

CONDUCTIVITY/TDS METER

Model : YK-22CT

- * Conductivity : 2 mS, 20 mS, 2 ranges.
- * TDS : 2,000, 20,000 PPM, 2 ranges.
- * Temp. : 0 to 60.0 $^{\circ}$ C, $^{\circ}$ C/ $^{\circ}$ F.
- * ATC, Hold, Record (Max., Min.).
- * RS232/USB computer interface.



CONDUCTIVITY METER, wide range

Model : CD-4306

- * Wide ranges conductivity meter.
- * 4 ranges : 200 μ S, 2 mS, 20 mS, 200 mS.
- * 4 rings conductivity probe
- * Data hold.
- * RS232/USB computer interface.



CONDUCTIVITY METER

Model : YK-2004CD

- * Range : 200 μ S/2 mS/20 mS/200 mS.
- * Automatic temp. compensation, ATC factor adj.
- * Carbon rod electrode for long life.
- * Max., Min., Data hold, zero adjust.
- * RS232/USB computer interface.
- * Jumbo LCD, unit with dot matrix display.
- * DC 1.5V (UM-3, AA) x 4 PCs or DC 9V adapter in.
- * Size : 203 x 76 x 38 mm.



Model : YK-2014CD

YK-2004CD probe
YK-2014CD probe



CONDUCTIVITY METER

Model : PCD-431

- * 2 ranges : 2,000 μ S, 20 mS.
- * Temperature measurement, $^{\circ}$ C/ $^{\circ}$ F.
- * Automatic temperature compensation.
- * Probe with the meter, all in one.
- * Carbon rod electrode, high reliability.
- * Data hold, Record (max., min.).
- * IP-67 Water resistance, heavy duty.
- * External calibration buttons.
- * DC 1.5V battery (UM-4, AAA) x 4.



CONDUCTIVITY METER

Model : CD-4301

- * 4 ranges: 200 μ S, 2mS, 20mS, 200mS.
- * Automatic temperature compensation.



CONDUCTIVITY METER, pocket

Model : CD-4302

- * 2 ranges : 0 -1.999 mS, 2 -19.99 mS.
- * Automatic temperature compensation.



CONDUCTIVITY METER, ATC, two displays

Model : CD-4322

- * 2 ranges : 2 mS, 20 mS.
- * Temperature measurement, $^{\circ}$ C/ $^{\circ}$ F.
- * LCD display, pocket type.
- * Automatic temperature compensation.
- * 1600 Data logger point.
- * Separate probe, easy operation.
- * RS232/USB interface, Record.
- * DC 9V battery (006P) or DC 9V adapter in.



CONDUCTIVITY METER, pocket

Model : CD-4312

- * Range 1 : 0 - 1.999 mS.
- * Range 2 : 2 - 19.99 mS.
- * Automatic temperature compensation.
- * Data hold.



1.413 mS
Conductivity solution
Model : CD-14