

20 Cocopan Crescent, Driehoek, Germiston Gauteng, South Africa Tel: +27 11 873 1311 FAX:+27 11 873 2396 Web: www.eurocel.it

# PRODUCT INFORMATION **EUROCEL STATIONERY TAPE**

## **DESCRIPTION**

Single sided transparent tape.

### **PRODUCT DATA**

Backing	0.023mm BOPP film	
Adhesive	Water based acrylic	

	Unit	Average Value	Method
Total thickness	mm	0.038	PSTC 133
Adhesion to steel	N/25mm	5	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	140	PSTC 131
Temp. Resistance	°C	15°C – 33°C	=

#### **APPLICATION**

Single sided tape fit for school, office, stationery and home applications. Suitable for general purpose uses, easy unwinding and tear. Available in 33m, 50m, and 66m lengths.

Features	Benefits		
Water based acrylic adhesive	✓ High tack	✓ Performing well in most common uses	
BOPP backing	✓ Easy to use	✓ Hand tearable	

### **CONDITIONS OF USE AND CONFORMITY**

Product shelf life and storage: 12 months; based on the product being stored at 15°C to 25°C with max. relative humidity of 65% out of direct sunlight. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature is lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

