

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorization is granted. Violation will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、注册、其他知识产权等权益外，本公司保留对涉及发明、实用新型、外观设计、发明专利、软件著作权、商标、注册、其他知识产权等权益的所有权利。

FOR-1755 Rev.1.7

2

3



4

5

6

未注公差/General tolerances (mm)




0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500		±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



Note:

The A&Z(H) in the name means: A(H) and Z(H).

6	Screw	Steel	M3/Zn Plated
5	Pin	Copper	Sn Plated
4	Cage	Copper alloy	M3/Ni Plated
3	2EDG-DIN35	PA66	UL94V-0
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		300/15	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2
额定电压/电流/Rated Voltage(V)/Current(A)		250/12	320/12
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		4	4
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M3, 0.6/5.16	
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		28~12/ 0.2~2.5	
间距/Pitch(mm)/线数范围/Poles		5.08/N=02~24P	
剥线长度/Stripping length(mm)		7~8	
使用温度范围/Operating temperature(°C)		-40~-+105	
符合RoHS环保要求/Conform to RoHS		Yes	



			MATERIAL:		SURFACE/COLOR:		
			MAT NO./REV: - / 00		MAT STATUS: 批量		
APPD:	兰春华	2022.12.01	NAME				
CHKD:	龚耀志	2022.12.01	2EDG-UDB-5.08-XXP-1Y-00A&Z(H)				
DRFT:	朱岳鹏	2022.12.01	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
	A4		200020105	CUSTOMER DRAWING	已发布	1:1	1/1

00			朱岳鹏	2022.12.01
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6