

# LOCKABLE ISOLATOR SWITCHES

## PANEL MOUNT



**3,4 OR 6 POLE**  
**16 – 160 AMP**  
**5.5kW—75kW**

## ENCLOSED



**2 – 4 OR 6 POLE**  
**16 – 160 AMP**  
**5.5kW—75kW**



**SPECIAL CONFIGURATION SWITCHES MADE TO ORDER**

# PRODUCT INTRODUCTION

This range of rotary switches mainly apply to 440v and below, AC 50Hz or 240V and below DC circuits. For breaking and closing, change-over of circuits under infrequently manual operation.

The typical applications are:

- Maintenance, repair and safety switches
- ON/OFF switches
- Main switches
- Control switches
- Panic switches
- Manual/Automatic switches

This range complies with GB 14048.3, GB 14048.5 and IEC 60947-3, IEC 60947-5-1

The range currently has 8 ratings; 16A, 20A, 25A, 32A, 40A, 63A, 125A and 160A

## SPECIFICATIONS

	16A	20A	25A	32A	40A	63A	125A	160A
Rated insulation Voltage $U_i$ V	660/ 690	660/ 690	660/ 690	660/ 690	660/ 690	660/ 690	660/ 690	660/ 690
Rated Thermal Current $I_{th}$ A	16	20	25	32	40	63	125	160