



|                        |               |
|------------------------|---------------|
| Product Size           | 150ml         |
| Gross Weight           | 153g          |
| Net Weight             | 113g          |
| UN Number              | 1950          |
| Custom Code            | 3403.19.00    |
| Country of Manufacture | RSA           |
| Barcode                | 6001690300665 |
| Article Number         | 030066        |

| CHARACTERISTICS |          |
|-----------------|----------|
| Colour          | Clear    |
| Texture         | Liquid   |
| Odour           | Aromatic |
| Temp Range      | <=35 °C  |

| PACKAGING       |                      |
|-----------------|----------------------|
| Type            | Card Box             |
| Dimensions      | H:14.5 W:22 L:32.5cm |
| Box Weight      | 4kg                  |
| Packaging Group | Class II             |
| Valve Type      | 360°                 |
| Cap             | Translucent Blue     |
| Pack Type       | Aerosol              |
| Units in Carton | 24                   |

### Product Description

- ✔ **ANTI-STATIC LUBRICANT**
- ✔ **WATERPROOFS & INSULATES**
- ✔ **INHIBITS CORROSION**
- ✔ **PROTECTS**

Q8 SILICONE SPRAY is a high quality silicone spray that waterproofs and insulates electrical components, protects rubber and plastic components, inhibits rust and corrosion and is an anti static lubricant.

Available in 150 ml / 400 ml / 5 lt / 20 lt / 1000 lt

### Ideal Usage



## Application of Product

### Directions:

Shake well before use. Q8 SILICONE SPRAY works best when the nozzle is pressed down firmly. Hold the can 25 cm away from area to be sprayed. Hold can in any position. Ensure that the surface to be sprayed is clean and dry. Use on electrical systems. Lubricates switchgears and prevents arcing. Prevents battery terminal corrosion. A non-staining lubricant for clips, hinges, rubber bushes and plastic fittings. Ideal for protecting vinyl and plastic surfaces.

## Test Results/Approvals/Certificates

N/A

## Safety Data Sheet Summary

### Health/ Routes of entry

**Threshold limit value:** Hydrocarbon solvent lowest TVL(100ppm)

### Symptoms of exposure

**Inhalation** May cause anaesthesia, headache, dizziness, nausea and upper respiratory irritation

**Skin contact:** May cause drying of skin and/or irritation

**Eye contact:** May cause irritation, tears and redness

**Ingestion:** May cause irritation, nausea, vomiting and diarrhea

**DANGER** if swallowed can enter lungs and may cause chemical pneumonia. Do not induce vomiting. Obtain medical assistance.