

UT58B Modern Digital Multimeters

SPECIFICATIONS



UL/CUL Pending

Registered Design No.: 0211977.6M001

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+1)
AC Voltage	2V/20V/200V/1000V	±(0.8%+3)
DC Current	2mA/20mA/200mA/20A	±(0.8%+1)
AC Current	2mA/200mA/20A	±(1%+3)
Resistance	200Ω/2kΩ/20kΩ/2MΩ/20MΩ/200ΩM	±(0.8%+1)
Capacitance	2nF/200nF/100μF	±(4%+3)
Temperature(°C)	-40°C ~ 1000°C	±(1%+3)
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max Display	1999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54mm
Product Colour	Body- Grey, Holster - Red
Product Net Weight	351g (including holster)
Product Size	179 x 88 x 39mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Test Clip, Multi-Purpose Socket, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	508 x 433 x 326mm (0.072CBM Per Standard Carton)
Standard Carton Gross Weight	22kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.