

# UNI-T

## UTP3702



### SPECIFICATIONS

Feature		UTP3702
Output Voltage	Ch1, Ch2	0~32V
	Ch3	
Output Current	Ch1, Ch2	0~3A
	Ch3	
Overload Effect	CV $\leq$ 1 x 10 <sup>-4</sup> + 2mV, CC $\leq$ 2mA	
Ripple & Noise	CV $\leq$ 1mVrms, CC $\leq$ 1mArms	
Regulation	CV - 20mV (Typical Value), CC - 50mV (Typical Value)	
Tracking Error	5 x 10 <sup>-3</sup> + 2mV	
Reliability	MTBF (e): $\geq$ 2000 hours	
Other Features	Triple Output, Series or Parallel Operation, Current Limitation Auto Switching Between Voltage and Current Operation	

### GENERAL CHARACTERISTICS

Power	220V $\pm$ 10%, 50Hz $\pm$ 4%
Product Color	Red and Grey
Product Net Weight	Around 4kg
Product Size	210mm x 152mm x 305mm
Standard Accessories	English Manual and Power Cord
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	600 x 380 x 245mm (0.056 CBM Per Export Carton)
Standard Carton Gross Weight	9.5kg