

Antimicrobial Switches - 1500 Standard & 1300 High Inrush

rocker switches



- ▶ Standard rocker switch
- ▶ Non-illuminated
- ▶ 1300 high inrush current
- ▶ Choice of switching circuits including 3 position
- ▶ Choice of bezel styles
- ▶ Choice of panel cut outs
- ▶ Matching indicator
- ▶ Single pole
- ▶ Splash resistant option
- ▶ BioCote antimicrobial option
- ▶ Panel cut out 'A' style: 27.3 x 12.3mm



In house test



In house test



1500 Series 16(4)A 250Vac T125

UL CSA 16A Non Ind 250Vac, (2 posn) 250Vac 1hp, 125Vac 1/2hp, (3 posn) 250Vac 1/2hp, 125Vac 1/4hp
UL 10A 14Vdc 'T' (1500 and 1510 only)
UL 85°C, file E45221, CSA file LR10990

10A 24Vdc

1300 series 16(6)A 250Vac T125 5E4 (50,000 Ops.)
150A Inrush to EN61058-1

UL CSA 20A 250Vac 1hp, 125Vac 1/2hp
UL 85°C, file E45221, CSA file LR10990

20A 24Vdc

RoHS compliant

BioCote antimicrobial additive. Independently verified.

3mm contact gap except if marked μ .

Technical data on pages 4 & 5 (switches), 6 (indicators).

C 1300 A L--- B

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, VOLTAGE ETC BioCote

TERMINAL	FUNCTION	ROCKER																																				
<p>C</p> <p>6.3 x 0.8</p>	<p>Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 1</p> <table border="1"> <tr> <td>Standard 1500</td> <td>High Inrush 1300 <small>*L' body only Approvals apply to C & T terminals only</small></td> <td>ON - OFF</td> <td></td> </tr> <tr> <td>1501 <small>HP rating N/A</small></td> <td></td> <td>ON - OFF (momentary ON)</td> <td></td> </tr> <tr> <td>1502 <small>HP rating N/A</small></td> <td></td> <td>ON - OFF (momentary OFF)</td> <td></td> </tr> <tr> <td>1510 μ <small>HP rating N/A</small></td> <td></td> <td>ON - ON</td> <td></td> </tr> <tr> <td>1511 μ <small>HP rating N/A</small></td> <td></td> <td>ON - ON (momentary 1 side)</td> <td></td> </tr> <tr> <td>1520 μ <small>125V & 250V 1/2 HP H terminal rated T100 only</small></td> <td></td> <td>ON - OFF - ON</td> <td></td> </tr> <tr> <td>1521 μ <small>HP rating N/A H terminal rated T100 only</small></td> <td></td> <td>ON - OFF - ON (momentary 1 side)</td> <td></td> </tr> <tr> <td>1522 μ <small>HP rating N/A H terminal rated T100 only</small></td> <td></td> <td>ON - OFF - ON (momentary 2 sides)</td> <td></td> </tr> <tr> <td>0430 <small>X terminal N/A</small></td> <td></td> <td>Indicator Technical data on page 6</td> <td></td> </tr> </table>	Standard 1500	High Inrush 1300 <small>*L' body only Approvals apply to C & T terminals only</small>	ON - OFF		1501 <small>HP rating N/A</small>		ON - OFF (momentary ON)		1502 <small>HP rating N/A</small>		ON - OFF (momentary OFF)		1510 μ <small>HP rating N/A</small>		ON - ON		1511 μ <small>HP rating N/A</small>		ON - ON (momentary 1 side)		1520 μ <small>125V & 250V 1/2 HP H terminal rated T100 only</small>		ON - OFF - ON		1521 μ <small>HP rating N/A H terminal rated T100 only</small>		ON - OFF - ON (momentary 1 side)		1522 μ <small>HP rating N/A H terminal rated T100 only</small>		ON - OFF - ON (momentary 2 sides)		0430 <small>X terminal N/A</small>		Indicator Technical data on page 6		<p>A Softline Matt</p> <p>B Splash resistant (with Arcshield) Matt</p> <p>H Slotted (for custom Adaptors) not momentary</p> <p>V Curved Matt or gloss</p> <p>W Splash resistant (with Arcshield) Matt</p> <p>X Two colour Matt ON - OFF only (not momentary)</p> <p>F Flat lens Gloss (0430 only)</p> <p>A Softline lens Matt (0430 only) as F but with raised profile</p>
Standard 1500		High Inrush 1300 <small>*L' body only Approvals apply to C & T terminals only</small>	ON - OFF																																			
1501 <small>HP rating N/A</small>			ON - OFF (momentary ON)																																			
1502 <small>HP rating N/A</small>			ON - OFF (momentary OFF)																																			
1510 μ <small>HP rating N/A</small>			ON - ON																																			
1511 μ <small>HP rating N/A</small>			ON - ON (momentary 1 side)																																			
1520 μ <small>125V & 250V 1/2 HP H terminal rated T100 only</small>			ON - OFF - ON																																			
1521 μ <small>HP rating N/A H terminal rated T100 only</small>			ON - OFF - ON (momentary 1 side)																																			
1522 μ <small>HP rating N/A H terminal rated T100 only</small>			ON - OFF - ON (momentary 2 sides)																																			
0430 <small>X terminal N/A</small>			Indicator Technical data on page 6																																			
<p>H</p> <p>4.8 x 0.8*</p>																																						
<p>K</p> <p>2.8 x 0.8*</p>																																						
<p>T</p> <p>02.1 Solder</p>																																						
<p>U</p> <p>02.1 Right angle "T" solder terminal</p>																																						
<p>X</p> <p>4.0 PCB 0.8Sq* *N/A for 1300 series</p>																																						