




MMCX Connectors


M52300

MMCX MALE CRIMP TYPE
(RG174U/178U)
(GOLD PLATED)




M52380

RIGHT ANGLE MMCX FEMALE PCB MOUNT
(GOLD PLATED)




M52306

RIGHT ANGLE MMCX MALE CRIMP TYPE
(RG174U/178U)
(GOLD PLATED)




M52400

MMCX MALE TO SMA FEMALE
(GOLD PLATED)




M52310

MMCX FEMALE CRIMP TYPE
(RG174U/178U)
(GOLD PLATED)




M52410

MMCX FEMALE TO SMA FEMALE
(GOLD PLATED)




M52316

MMCX FEMALE BULKHEAD CRIMP TYPE
(RG174U/178U)
(GOLD PLATED)




M52430

MMCX FEMALE BULKHEAD
(GOLD PLATED)




M52360

MMCX MALE PCB MOUNT
(GOLD PLATED)




M52460

MMCX MALE SOLDER TYPE
FOR SEMI-RIGID CABLE
(RG405U)
(GOLD PLATED)




M52370

MMCX FEMALE PCB MOUNT
(GOLD PLATED)




M52462

RIGHT ANGLE MMCX MALE SOLDER TYPE
FOR SEMI-RIGID CABLE
(RG405U)
(GOLD PLATED)




M52376

MMCX FEMALE PCB MOUNT
(GOLD PLATED)



M52466

MMCX FEMALE SOLDER TYPE
FOR SEMI-RIGID CABLE
(RG405U)
(GOLD PLATED)



ELECTRICAL SPECIFICATIONS :

Connector Series	Impedance	Frequency Range	Voltage Rating	Withstanding Voltage	Contact Resistance	Insulation Resistance
MMCX	50Ω	0 - 6 GHz	AC 170V	AC 500V one minute	5.0mΩ max	1000MΩ min at DC 500V