



20 Cocopan Crescent, Driehoek, Germiston  
Gauteng, South Africa  
Tel: +27 11 873 1311 FAX: +27 11 873 2396  
Web: www.eurocel.it

Sicad South Africa (PTY) LTD

## PRODUCT INFORMATION

# EUROCEL SECURITY PRINTED PAPER TAPE

### DESCRIPTION

Printed paper carton sealing tape for packaging.

### PRODUCT DATA

Backing	0.058mm saturated paper
Adhesive	Natural rubber and resins based

	Unit	Average Value	Method
Total thickness	mm	0.120	PSTC 133
Adhesion to steel	N/25mm	3.3	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	7	PSTC 131
Temp. Resistance	°C	60°C	=

### APPLICATION

Printed paper carton sealing tape for standard packaging. Printable (not in negative) or available printed up to 3 colours (30% max printable surface). Tape must be applied at room temperature.

Features	Benefits	
Natural rubber and resins-based adhesive	✓ Good adhesion even on different types of cardboard	✓ Good adhesion even if stored in cold temperature after closing
Saturated paper backing	✓ Resistant to box shock ✓ Hand tearable	✓ Identifies pilferage (as damaged cartons would be recognized if resealable were attempted)

### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; based on the product being stored at 15°C to 25°C with max. relative humidity of 65% out of direct sunlight. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature is lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.