





SECTION A-A

NOTES:

1. Operation Temperature: -40°C ~ +85°C.
2. Electrical Characteristics:
 - 2.1) Rated Current: 125V AC, 1.5A@25°C.
 - 2.2) Contact Resistance: 20mΩ Max.
 - 2.3) Insulation Resistance: 500MΩ Min, 100V DC/min.
 - 2.4) Voltage Proof: 1000V AC/1 minute no breakdown.
3. Mechanical Characteristics:
 - 3.1) Insertion Force & Withdrawal Force: 30N Max.
 - 3.2) Durability: 750 cycles Min.
4. Environmental compliance:
 - 4.1) the products are compliant with the RoHS, and REACH etc.



说明:

1. 使用温度范围: -40°C ~ +85°C.
2. 电气特性:
 - 2.1) 电压、电流规格: 125V AC 1.5A@25°C.
 - 2.2) 接触电阻: 20mΩ 最大.
 - 2.3) 绝缘电阻: 500MΩ 至少 100V DC/分钟.
 - 2.4) 耐电压: 1000V AC/分钟, 无击穿.
3. 机械特性:
 - 3.1) 插入力&拔出力: 30N 最大.
 - 3.2) 耐久性: 750次至少.
4. 环保符合性:
 - 4.1) 产品符合RoHS, REACH等环保规格.