


接线图/WIRING DIAGRAM



励磁顺序(2相励磁) VS. 旋转方向  
EXCITING SEQUENCE (TWO PHASES)  
VS. DIRECTION OF ROTATION

STEP	A	B	$\bar{A}$	$\bar{B}$	
1	+	+	-	-	↓ CW ↑ CCW
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

从安装面看为顺时针方向  
CLOCKWISE VIEW FROM MOUNTING SIDE

电气特性参数/ELECTRICAL PARAMETER

步距角/STEP ANGEL	1.8° ±5%	备注/(NOTE):  减速比 1:10
相数/NO. OF PHASES	2	
电压/RATED VOLTAGE	3.0 V	
电流/RATED CURRENT	3.0 A	
电阻/RESISTANCE	1.0 ohm±10% AT 20° C	
电感/INDUCTANCE	4.0 mH±20% AT 1kHz, 1Vrms	
静转矩/HOLDING TORQUE	1.9 N.m以上/MIN.	
定位转矩/DETENT TORQUE	6.0 N.cm以下/Max	
转动惯量/ROTOR INERTIA	480 g.cm <sup>2</sup>	
引出线规格/LEAD STYLE	AWG22 UL1007	
绝缘等级/INSULATION CLASS	CLASS B	
绝缘耐压/DIELECTRIC STRENGTH	500V A.C 1分钟/MINUTE	
绝缘电阻/INSULATION RESISTANCE	100 MΩ 以上/MIN.	



				技术规格书 TECHNICAL SPECIFICATION		WANTAI MOTOR www.wantmotor.com	
						一般公差 TOLERANCE ±0.3/±0.3°	
设计/DESIGNED		JIN 2021.11.30		型号 MODEL		比例 SCALE 1:1	
审核/CHECKED		ANDY 2021.11.30		57BYGH627AG10-XM		单位 UNIT mm	
工艺/TECHNICS				编码 CODE		三视图 THIRD ANGLE PROJECTION	
批准/APPROVED						页 SHEET 1/1	