



GMX

Medium Time Lag Glass Tube Fuses

- 5Øx25 mm (0.197x0.98 inch)
- Ampere Rating: 100mA to 20 A
- Voltage Rating: 250V and less
- **Electrical Characteristics:**
210% - 30 Minutes, **Maximum**
400% - 0.3 Seconds, **Maximum**
1000% - 5 mS Minimum
- **Standards:** DIN 41576



GMJ

Medium Time Lag Glass Tube Fuses

- 5Øx30 mm (0.197x1.18 inch)
- Ampere Rating: 100mA to 20 A
- Voltage Rating: 250V and less
- **Electrical Characteristics:**
210% - 30 Minutes, **Maximum**
400% - 0.3 Seconds, **Maximum**
1000% - 5 mS Minimum
- **Standards:** DIN 41576



AWE AWP-A

AWE

Fast Acting Glass Tube Fuses

- 6.3Øx22.2 mm (1/4x7/8 inch)
- Ampere Rating: 10mA to 30 A
- Voltage Rating: 250V and less
- **Electrical Characteristics:**
135% - 1 Hour, **Maximum**
200% - 5 Seconds, **Maximum**
- Pig-Tail Lead(**AWP**):
Tinned Copper Wire
0.8Ø mm- < 13A
1.0Ø mm- ≥ 13A < 20A
1.2Ø mm- ≥ 20A
- **Standards:** UL Listed 198G,
CSA Certified C22.2N59



AAE AAP

AAE

Fast Acting Glass Tube Fuses

- 6.3Øx15.9 mm (1/4x5/8 inch)
- Ampere Rating: 63mA to 30 A
- Voltage Rating: 250V and less
- **Electrical Characteristics:**
135% - 1 Hour, **Maximum**
200% - 5 Seconds, **Maximum**
- Pig-Tail Lead(**AAP**):
Tinned Copper Wire
0.8Ø mm- < 13A
1.0Ø mm- ≥ 13A < 20A
1.2Ø mm- ≥ 20A
- **Approvals:**
AAE
63mA~3.5A, 250V
AAP-A
3.5A and less, 125V



AXE

Fast Acting For Instrument Glass Tube Fuses

- 6.3Øx25.4 mm (1/4 x1 inch)
- Ampere Rating: 10mA to 30A
- Voltage Rating: 250V and less
- **Electrical Characteristics :**
135% - 1 Hour, **Maximum**
200% - 10 Seconds, **Maximum**
- **Approvals:**

20A and less



AXP-A

Fast Acting Glass Tube Fuses With Pig-Tail

- 6.3Øx25.4 mm (1/4 x1 inch)
- Ampere Rating: 10mA to 30A
- Voltage Rating: 250V and less
- **Electrical Characteristics :**
135% - 1 Hour, **Maximum**
200% - 10 Seconds, **Maximum**
- Pig-Tail Lead:
Tinned Copper Wire
0.8Ø mm- < 13A
1.0Ø mm- ≥ 13A < 20A
1.2Ø mm- ≥ 20A
- **Approvals:**

10A and less



GBF

Very Fast Acting Ceramic Tube Fuses

- 5Øx20 mm (0.197x0.787 inch)
- Ampere Rating: 1 to 20 A
- Voltage Rating: 250V and less
- **Electrical Characteristics:**
135% - 2 Minutes, **Maximum**
250% - 0.2 Seconds, **Maximum**
- **Recommend For Protection:**
Solid-State Devices,
Semiconductors
- **Approvals:**

1A~20A, 250V



ABB

Super Fast Acting Ceramic Tube Fuses

- 6.3Øx32 mm (1/4x1-1/4 inch)
- Ampere Rating: 1 to 30 A
- Voltage Rating: 500V and less
- **Electrical Characteristics:**
135% - 2 Minutes, **Maximum**
250% - 0.2 Seconds, **Maximum**
- **Recommend For Protection:**
Solid-State Devices,
Semiconductors
- **Approvals:**

1A~30A, 500V