


Bi-Pin lamps

SAMCOLE CODE	LAMPBASE	SIZE (mm)	Voltage(V)	Current(mA)	M.S.C.P.	COLOR	FILAMENT	AVERAGE LIFE HRS	REMARK	TYPE	APPLICATION
132.113	BI-PIN	3.2x9.5mm/T-1	5	21		Clear	C-2R	10000	1.27 or 2.54	BI-PIN	Sub-miniature
131.118	BI-PIN	3.2x9.5mm/T-1	5	60		Clear	C-2R	25000	1.27 or 2.54	BI-PIN	Sub-miniature
132.240	BI-PIN	3.2x9.5mm/T-1	12	60		Clear	C-2F	10000	1.27 or 2.54	BI-PIN	Sub-miniature
131.288	BI-PIN	3.2x9.5mm/T-1	14	65		Clear	C-2F	10000	1.27 or 2.54	BI-PIN	Sub-miniature
131.374	BI-PIN	3.2x9.5mm/T-1	28	24		Clear	CC-2F	4000	1.27 or 2.54	BI-PIN	Sub-miniature
132.409	BI-PIN	3.2x9.5mm/T-1	36	20		Clear	CC-2F	5000	1.27 or 2.54	BI-PIN	Sub-miniature
134.378	BI-PIN	4.5x15.25mm/T-1 1/4	28	40	0.32	Clear	C-2F	1000	2.54 or 3.17	BI-PIN	Sub-miniature
135.148	BI-PIN	5.7x16mm/T-1 3/4	6	200	0.6	Clear	C-2R	1000	3.17	BI-PIN	Sub-miniature
135.184	BI-PIN	5.7x16mm/T-1 3/4	6.3	200	0.55	Clear	C-2R	5000	3.17	BI-PIN	Sub-miniature
135.238	BI-PIN	5.7x16mm/T-1 3/4	12	40	0.12	Clear	C-2F	10000	3.17	BI-PIN	Sub-miniature
135.310	BI-PIN	5.7x16mm/T-1 3/4	18	40	0.15	Clear	C-2F	10000	3.17	BI-PIN	Sub-miniature
135.366	BI-PIN	5.7x16mm/T-1 3/4	24	50	0.05	Clear	C-2F	1000	3.17	BI-PIN	Sub-miniature
135.378	BI-PIN	5.7x16mm/T-1 3/4	28	40		Clear	C-2F		3.17	BI-PIN	Sub-miniature
135.381	BI-PIN	5.7x16mm/T-1 3/4	28	60	0.34	Clear	C-2F	25000	3.17	BI-PIN	Sub-miniature
135.382	BI-PIN	5.7x16mm/T-1 3/4	28	65	0.65	Clear	C-2F	5000	3.17	BI-PIN	Sub-miniature