



Waterproof Ceiling Fan Capacitor

Waterproof ceiling fan capacitor Features of ceiling fan capacitor: 1. Rectangle flame retardant plastic case, epoxy resin packaging; 2. Small size, light weight, easy to set up; 3. Low dissipation factor, good insulation; 4. Personalized equipment, high reliability.

Promote medicine

Characteristics of ceiling fan capacitor:

1. Rectangle flame recovery plastic case, epoxy resin packaging;
2. Small size, light weight, easy to set up;
3. Low dissipation factor, good insulation;
4. Self-correcting, reliable and reliable equipment;
5. Suitable for electric fans, exhaust fans, generators, pumps and more, great for starting and running on AC motor.

Special specification of this ceiling fan capacitor

Model: CBB61
 Working Temperature: -25 to + 70 ° C
 Working Frequency: 50 / 60Hz
 Temperature: 450VAC
 Tolerance: ± 5%
 Rated Capacitance: 1uf
 Color: Black
 Type: Metal Polypropylene Film Capacitor
 Metal: 2 wires

(Specification) of cbb61 fan, fan, fan motor motor body film capacitors

Capacitance range	0.47µF-35µF
Capacitance Tolerance	± 5% or as required
Rated Replacement	125VAC, 250AC, 350AC, 400VAC, 440VAC, 450VAC, 500VAC
Rated Frequency	50/60 Hz
The Exit Point	≤0.002
Operating Temp.	-40 °C ~ + 85 °C or -25 °C ~ + 70 °C
Dielectric	Polypropylene with self-healing SH
Insulation Resistance	≥3000S
Cloud Stop	40/85/21, 25/70/21
Normal voltage (Terminal to Terminal)	2 X Voltage
Hold voltage (Terminal for Case)	At least 2000 V AC for 1 Min.
Ref. Contents	IEC60252-1: 2001
Good Energy	ISO 9001: 2008
Certificate	CQC, CE
Application	fan, fan, blower



Yueqing Chirx Electron Co., Ltd

Our company is one of the leading companies in Wenzhou and is an important partner in the Chinese Capacitor.

(Specification) of cbb61 fan, fan, fan motor motor film capacitors

CBB61				
Capacity (μF)	250V	350-400	450V	500-630v
0.47	32 * 10 * 20	36 * 10 * 20	37 * 11 * 24	37 * 11 * 24
0.68	32 * 10 * 20	36 * 10 * 20	37 * 11 * 24	37 * 11 * 24
1	32 * 10 * 20	37 * 11 * 20	37 * 11 * 24	37 * 13 * 24
1.2	32 * 10 * 20	36 * 11 * 22	37 * 11 * 24	37 * 13 * 24
1.25	32 * 10 * 20	36 * 11 * 22	37 * 11 * 24	37 * 13 * 24
1.5	36 * 10 * 20	37 * 13 * 24	37 * 13 * 24	37 * 14 * 25
1.8	36 * 10 * 20	37 * 13 * 24	37 * 14 * 25	37 * 17 * 28
2	36 * 10 * 20	37 * 14 * 25	38 * 15 * 25	38 * 18.5 * 29
2.2	36 * 10 * 20	37 * 14 * 25	38 * 15 * 25	38 * 18.5 * 29
2.4	37 * 13 * 24	38 * 15 * 25	38 * 15 * 25	38 * 20 * 30
2.5	37 * 13 * 24	38 * 15 * 25	37 * 16 * 29	38 * 20 * 30
2.75	37 * 13 * 24	38 * 15 * 25	37 * 16 * 29	47 * 17.5 * 34.5
3	37 * 13 * 24	38 * 15 * 25	38 * 20 * 30	47 * 17.5 * 34.5
3.3	37 * 14 * 25	38 * 17 * 28	38 * 20 * 30	47 * 19 * 31
3.5	37 * 14 * 25	38 * 18.5 * 29	38 * 20 * 30	47 * 17.5 * 34.5
3.75	37 * 14 * 25	38 * 18.5 * 29	47 * 17 * 28	47 * 17.5 * 34.5
4	38 * 15 * 25	47 * 17 * 28	47 * 17 * 28	47 * 20 * 37.5
4.25	38 * 15 * 25	47 * 17 * 28	47 * 17.5 * 33	47 * 20 * 37.5
4.5	38 * 15 * 25	47 * 17 * 28	47 * 17.5 * 33	47 * 20 * 37.5
4.75	38 * 15 * 25	47 * 17.5 * 34.5	47 * 17.5 * 33	47 * 23 * 35
5	38 * 15 * 25	47 * 19 * 33	47 * 17.5 * 33	47 * 23 * 35
5.5	38 * 15 * 25	47 * 19 * 33	47 * 19 * 33	47 * 25 * 35
6	38 * 15 * 25	47 * 19 * 33	47 * 20 * 37.5	47 * 23 * 41
6.5	37 * 17 * 28	47 * 19 * 33	47 * 25 * 35	47 * 25 * 42
7	47 * 17 * 28	47 * 20 * 37.5	47 * 25 * 35	47 * 25 * 42
7.5	47 * 17 * 28	47 * 20 * 37.5	47 * 25 * 35	47 * 25 * 42
8	47 * 17 * 28	47 * 23 * 35	47 * 25 * 35	58 * 25 * 42
9	47 * 19 * 33	47 * 25 * 35	47 * 25 * 42.5	58 * 25 * 42
10	47 * 19 * 33	47 * 25 * 35	47 * 25 * 42.5	58 * 25 * 42
12	47 * 20 * 37	47 * 25 * 42.5	58 * 25 * 42	58 * 28 * 50
13	47 * 20 * 37	58 * 25 * 42	58 * 25 * 42	58 * 28 * 50
14	47 * 20 * 37	58 * 25 * 42	58 * 28 * 50	58 * 31 * 57
15	47 * 23 * 35	58 * 25 * 42	58 * 28 * 50	58 * 31 * 57
16	47 * 23 * 35	57 * 32 * 44	58 * 28 * 50	58 * 31 * 57
18	47 * 23 * 41	57 * 32 * 44	58 * 31 * 57	
20	47 * 25 * 43	57 * 32 * 44	58 * 31 * 57	
22	58 * 25 * 42	57 * 32 * 44		
24	58 * 25 * 42	57 * 32 * 44		
25	58 * 25 * 42	58 * 28 * 50		
30	58 * 25 * 42			
35	58 * 25 * 42			