





安装面板
PANEL CUT-OUT



电路图 Circuit



主要技术参数、性能

The Main Technology Performance

项目 Item	参数 Parameter
额定电压、电压 Rated voltage Rated current	0.5A 125VAC
绝缘电阻 Insulated resistance	DC 500V 100MΩ min
接触电阻 Contact resistance	50Ω Max
介电强度(耐压) Dielectric strength	AC 1500V 1 minute
操作温度 Operating Temperature	-25℃ ~ +85℃
电寿命 Electrical Life	≥10000 Cycles

名称 NAME	数量 QTY	材料 MATERIAL	表面处理 FINISHING
弹簧 Spring	1	Spring steel wire 弹簧钢线 0.5mm	
接触片 Contact	1	Brass Plated steel	
脚 Lateral	2	Brass Plated steel	
底座 Bottom	1	PP	
壳体 Housing	1	Brass Plated steel	
头部 Button	1	PP	

版本	修订	更改内容
产品型号: DS-402	产品料号:	
产品系列 Part: Button Switch	规格:	物料:
物料比例: 2:1	日期: 2013.10.11	日期: 2013.10.11
请向本厂销售人员, 索取以下资料: 1. 1~02.0 2. 0~0.30 3. 0~0.18 4. 0~27零件 (mm)		
乐清市戴泰电子有限公司 YUEQING DAITER ELECTRON CO., LTD		