

SN7342B Solder pen (SN/PB:60/40) 0.8mm 15g
SN7342C Solder pen (SN/PB:60/40) 1.0mm 15g
SN73425C Solder pen (SN/CU:99.3/0.7) 1.0mm 10g




SN73449
 Lead free liquid flux
 Specific gravity : 0.794 (at 20°C)
 Acid value : 18.5mg KOH/g
 Solid content : 3.9%
 Flash point : 12°C



SN7343 B /C/D/F/G/H/K/L/M/Q Solder wire (SN/PB:60/40)
SN73435B /C/D/F/G/H/K/L/M/Q Solder wire (SN/CU:99.3/0.7)
 B : 0.5mm 250g
 C : 0.5mm 500g
 D : 0.5mm 1000g
 F : 0.8mm 250g
 G : 0.8mm 500g
 H : 0.8mm 1000g
 K : 1.0mm 250g
 L : 1.0mm 500g
 M : 1.0mm 1000g
 Q : 1.5mm 1000g



SN7345
 Soldering tip (long life tip)
 It is made of copper mixing with iron
 A:25W 3Ømm
 B:30W 4Ømm
 C:40W 5Ømm
 D:60W 6Ømm



SN7344
 Solder bar (SN/CU:99.9/0.1)
 Weight 1000g



SN7346
 Soldering tip
 It is made of copper mixing with nickel
 A:25W 3Ømm
 B:30W 4Ømm
 C:40W 5Ømm
 D:60W 6Ømm



SN73441 25Ømm Solder ball (SN/PB:60/40)
SN73442 25Ømm Solder ball (SN:99.95)



SN73470 110V
SN73471 220V
 Heating element
 A:25W 3Ø
 B:30W 4Ø
 C:40W 5Ø
 D:60W 6Ø



SN73443 0.6Ømm BGA sphere (SN/PB:63/37)
SN73444 0.6Ømm BGA sphere (SN/AG/CU:96.5/3/0.5)



SN7348
 Mini soldering pot (40Ø x 40mm)
 150W/250°C ~ 380°C

