

Non-insulated Cord end Terminals

Material: Purple copper

ITEM NO	Dimension(mm)				Cable size(mm ²)	
	L	Dφ	Cφ	W	A.W.G	mm ²
EN 0506	6.0	1.3	1.0	1.7	# 22	0.5
EN 0508	8.0					
EN 0510	10.0					
EN 0512	12.0					
EN 7506	6.0	1.5	1.2	1.9	# 20	0.75
EN 7508	8.0					
EN 7510	10.0					
EN 7512	12.0					
EN 1006	6.0	1.7	1.4	2.2	# 18	1.0
EN 1008	8.0					
EN 1010	10.0					
EN 1012	12.0					
EN 1507	7.0	2.0	1.7	2.5	# 16	1.5
EN 1508	8.0					
EN 1510	10.0					
EN 1512	12.0					
EN 1518	18.0					
EN 2507	7.0	2.6	2.2	3.3	# 14	2.5
EN 2508	8.0					
EN 2510	10.0					
EN 2512	12.0					
EN 2518	18.0					
EN 4009	9.0	3.2	2.8	3.9	# 12	4.0
EN 4012	12.0					
EN 4018	18.0					
EN 6010	10.0	3.9	3.5	4.8	# 10	6.0
EN 6012	12.0					
EN 6015	15.0					
EN 6018	18.0					
EN 10-12	12.0	4.9	4.5	5.8	# 7	10.0
EN 10-15	15.0					
EN 10-18	18.0					
EN 16-12	12.0	6.2	5.8	7.2	# 5	16.0
EN 16-15	15.0					
EN 16-18	18.0					
EN 25-16	16.0	7.9	7.5	9.1	# 4	25.0
EN 25-22	22.0					
EN 35-16	16.0	8.7	8.3	10.2	# 2	35.0
EN 35-25	25.0					
EN 50-20	20.0	10.9	10.3	12.4	# 1	50.0
EN 50-25	25.0					
EN 70-20	20.0	14.3	13.5	15.3	#210	70.0
EN 70-25	25.0					
EN 95-25	25.0	15.5	14.7	16.6	#310	95.0
EN 95-32	32.0					
EN 120-30	30.0	17.6	16.7	18.6	#410	120.0
EN 120-32	32.0					
EN 150-27	27.0	20.5	19.5	21.50	250/300MCB	150.0
EN 150-32	32.0					

