

Nylon-fully Insulated Female Terminals

Cable size:0.5 ~ 1.5mm²(A.W.G.22 ~ 16) Max current:Imax=10A Temperature:105°C

Material:Copper Sheath:Nylon

ITEM NO	Connectin g spec.	Thickness of material	Dimension(mm)						Color
			W	F	L	B	Dφ	Cφ	
FDFN 1.25-187(5)	0.5×4.75	0.4	5.0	6.4	21.0	10.5	3.5	1.7	red
FDFN 1.25-187(8)	0.8×4.75	0.4	5.0	6.4	21.0	10.5	3.5	1.7	
FDFN 1.25-250	0.8×6.35	0.4	6.6	7.3	22.0	11.0	4.0	1.7	

Cable size:1.5 ~ 2.5mm²(A.W.G.16 ~ 14) Max current:Imax=15A Temperature:105°C

Material:Copper Sheath:Nylon

ITEM NO	Connectin g spec.	Thickness of material	Dimension(mm)						Color
			W	F	L	B	Dφ	Cφ	
FDFN 2-187(5)	0.8×4.75	0.4	5.0	6.4	21.0	10.5	4.2	2.3	blue
FDFN 2-187(8)	0.8×4.75	0.4	5.0	6.4	21.0	10.5	4.2	2.3	
FDFN 2-250	0.8×6.35	0.4	6.6	7.3	22.0	11.0	4.5	2.3	

Cable size:4 ~ 6mm²(A.W.G.12 ~ 10) Max current:Imax=24A Material:Copper Temperature:105°C

Material:Copper Sheath:Nylon

ITEM NO	Connectin g spec.	Thickness of material	Dimension(mm)						Color
			W	F	L	B	Dφ	Cφ	
FDFN 5.5-250	0.8×6.35	0.4	6.6	7.3	24.0	13.0	6.3	3.4	yellow

