

尼龙全绝缘护套骑背形公母插端子(加铜套)(适用于软线)

- 材质: 黄铜
- 护套: 尼龙
- 温度: 105℃
- 表面处理: 镀锡


Nylon-Fully Insulated Piggy Back Disconnect (Double Copper Sleeve)(Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Nylon
- Temperature: 105℃
- Plating: Tin



PIGGY BACK TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm ²)	最大电流 Max Current	连接规格 Connecting spec.	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color	
					W	W1	H	D	d	L		
PBDFN 1.25-250 D	22-16(0.5-1.5)	10A	0.8 x 6.35	0.4 x 2	6.6	6.35	11.5	3.8	1.7	22.0	红 red	
PBDFN 2-250 D	16-14(1.5-2.5)	15A	0.8 x 6.35		6.6	6.35	11.5	4.4	2.3	22.7	蓝 blue	
PBDFN 5.5-250 D	12-10(4-6)	24A	0.8 x 6.35		6.6	6.35	14.0	5.7	3.4	24.5	黄 yellow	



PVC全绝缘护套子弹形母插端子(适用于软线)

- 材质: 黄铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Fully Insulated Bullet Receptacles (Apply in flexible wire)

- Terminal Body: Brass
- Insulation: Vinyl
- Plating: Tin



FEMALE BULLET TERMINAL

型号 Item NO	导线截面 Cable Size A.W.G(mm ²)	最大电流 Max Current	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color	
				W	b	D	d	F	L		
FRD 1.25-156	0.5-1.5 (22-16)	10A	0.4	6.0	3.9	3.7	1.7	13.0	23.0	红 red	

型号 Item NO	导线截面 Cable Size A.W.G(mm ²)	最大电流 Max Current	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color	
				W	b	D	d	F	L		
FRD 2-156	1.5-2.5 (16-14)	15A	0.4	6.1	3.9	4.3	2.3	14.0	24.0	蓝 blue	
FRD 2-195				7.0	4.9	4.3	2.3	14.0			

型号 Item NO	导线截面 Cable Size A.W.G(mm ²)	最大电流 Max Current	材料厚度 Thickness of material	尺寸Dimension(mm)						颜色 Color	
				W	b	D	d	F	L		
FRD 5.5-195	4-6 (12-10)	24A	0.4	7.0	4.9	5.3	3.4	14.0	25.5	黄 yellow	