


Loudspeaker Cables



Cross section (mm ²)	2 x 0,5	2 x 0,5	2 x 0,75	2 x 0,75	2 x 1,5	2 x 1,5	2 x 2,5	2 x 2,5	2 x 4	2 x 4
Part no.	40180	40023	40181	40024	40182	40025	40183	40026	40184	40027

Cable structure

Conductor material: Copper litz wire, bare

Identification: Grooves

Cond. make-up	16 x 0,20	16 x 0,20	24 x 0,20	24 x 0,20	28 x 0,25	28 x 0,25	48 x 0,25	48 x 0,25	55 x 0,30	55 x 0,30
Insulation h x w mm	2,0 x 5,0	2,1 x 4,7	2,2 x 4,9	2,2 x 4,9	2,6 x 5,5	2,6 x 5,5	3,3 x 7,0	3,3 x 7,0	4,3 x 8,2	4,3 x 8,2
Sheath material	PVC	PVC								
Sheath colour	transparent	black/red								
Weight approx. kg / km	15	15	20	20	37	37	63	63	80	80

Electrical characteristics

Loop resistance max. (Ohm/km)	70	70	47	47	23	23	14	14	9	9
Capacitance pF/m	47	47	60	60	67	67	67	67	64	64
Inductance µH/m at										
1 kHz	0,7	0,67	0,61	0,61	0,54	0,54	0,54	0,54	0,58	0,58
10 kHz	0,8	0,79	0,73	0,73	0,59	0,59	0,62	0,62	0,65	0,65
100 kHz	0,8	0,85	0,73	0,73	0,59	0,59	0,62	0,62	0,65	0,65
1000 kHz	0,8	0,8	0,67	0,67	0,52	0,52	0,56	0,56	0,59	0,59
Copper weight kg/km	9,6	9,6	14,4	14,4	28,8	28,8	48,0	48,0	76,8	76,8

Cross section (mm ²)	2 x 1,5	2 x 2,5	2 x 4	2 x 6	2 x 10
Part no.	40185	40186	40187	40188	40189

Cable structure

Conductor material: Bare copper litz wire, highly flexible

Identification: Stripes

Cond. make-up	189 x 0,10	322 x 0,10	511 x 0,10	777 x 0,10	1273 x 0,10
Insulation h x w mm	3,1 x 6,5	3,6 x 7,5	5 x 10,2	6,1 x 12,5	7,0 x 15,0
Sheath material	PVC	PVC	PVC	PVC	PVC
Sheath colour	transparent	transparent	transparent	transparent	transparent
Weight approx. kg / km	41	60	79	136	254

Electrical characteristics

Loop resistance max. (Ohm/km)	23	14	9	6	3
Capacitance pF/m	67	53	50	54	59
Inductance µH/m at					
1 kHz	0,54	0,48	0,49	0,46	0,45
10 kHz	0,61	0,55	0,56	0,54	0,53
100 kHz	0,62	0,59	0,6	0,56	0,56
1000 kHz	0,55	0,54	0,56	0,53	0,52
Copper weight kg/km	28,8	48,0	76,8	115,2	192,0

Dimensions and specifications may be changed without prior notice. (RM01)

Note

The materials used in manufacture are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers.