## 1688

0113

Shenzhen Global Technology Co., Ltd

响应

GLOBAL VI

## USB Tester Digital DC Current Voltage Capacity Power Detector Power Bank Charging Indicator

借描

## Model: J7-T / 181132

Features::

Current measuring range: 0.00 ~ 5.10 A Power cumulative range: 0 ~ 9999.99 MWH Cumulative capacity range: 0-999.99 mah Power metering range: 0 ~ 299.999 W Timing maximum time: 0 ~ 999 H 59 M 59 S

Voltage measuring range: +3.3V ~ 30.0 V

Time to refresh rate: > 500 ms/time > 500 ms/times

Resolution precision: 0.01 V Resolution precision: 0.01 A Resolution precision: 0.001 Wh Precision: 0.001 Ah(New features) Resolution precision: 0.001 W Resolution precision: 1 S

USES the large-scale instrument of the same metal manganese copper low impedance sampling resistance is almost zero (1.5 mm diameter metal manganese bronze material < 5 mR, internal resistance is almost zero)

The button is used to select screen and holding it down will reset the Ah and Wh counters. Holding the button down when connecting power will enter the configuration and calibration menu. Product size: 65 x 22 x 14 mm Working temperature: - 10 ~ + 60 °C Working humidity: 10 ~ 80 The pressure of work: 80 ~ 106 kpa Net weight: 100g Voltage Display **Power Display** Capacity Display **Current Display** Key 6.091% 0.027Ah 0. 154Ah 0.01:19 USB Security Tester Working time display Quantity of electric charge Display