


HellermannTyton PRE-INSULATED TERMINALS

WIRE RANGE mm ²	STUD (mm)	RING R(E)	SPADE S(E)	PIN P(E)	BUTT UT(E)	BULLET		FLAT BLADE FB(E)	HOOK BLADE HB(E)	DISCONNECT		PIGGY-BACK PB(E)	FULLY INSULATED DISCONNECT		QUICK SPLICE (QS)	CLOSED END CONNECTORS (CE)	CRIMPING TOOLS
						MALE ULM(E)	FEMALE ULF(E)			MALE DM(E)	FEMALE DF(E)		MALE (F-DM)	FEMALE (F-DF)			
34 - 1,57 (SIZE 1)	10	1R10			1UT			1FB10 (10 x 2,3 mm)	1HB (4,6 mm)	1DM (6,4 mm)	1DF (6,4 mm)	1PB (6,4 mm)	TF1DF (6,4 mm)	CE1			
	8	1R8															
	6	1R6	156A†	1P10 (10 mm)		1UT	1ULM4 (4 mm)	1ULF4 (4 mm)	1FB11 (11 x 3,0 mm)	1HB3 (3 mm)	1DM4 (4,8 mm)	1DF4 (4,8 mm)	1PB	1QS			
	5	1R5	155A†														
	4	1R4	154A†							1DM2 (2,8 mm)	1DF2 (2,8 mm)		TF1DF2 (2,8 mm)				
	3,5		1535														
	3	1R3	153										F1DMY (6,4 mm Nylon)				
	1,17 - 3,24 (SIZE 2)	10	2R10			2UT			2FB9 (9 x 2,8 mm)	2HB (4,6 mm)	2DM (6,4 mm)	2DF (6,4 mm)	2PB (6,4 mm)	TF2DF (6,4 mm)		CE2	
		8	2R8														
		6	2R6	256A†	2P10 (10 mm)		2UT	2ULM4 (4 mm)	2ULF4 (4 mm)	2FB13 (13 x 2,4 mm)	2HB3 (3 mm)	2DM4 (4,8 mm)	2DF4 (4,8 mm)	2PB		2QS	
5		2R5	255A†	2P12 (12 mm)			2ULM5 (5 mm)	2ULF5 (5 mm)	2FB18 (18 x 2,2 mm)	2HB3 (3 mm)	2DM4 (4,8 mm)	2DF9 (9,4 mm)	F2DMY (6,4 mm Nylon)				
4		2R4(A)‡	254A†														
3,5		2R35	2535														
2,5 - 6,00 (SIZE 3)		12	3R12						3FB10 (10 x 2,8 mm)	3HB (4,6 mm)	3DM (6,4 mm)	3DF (6,4 mm)	3PB (6,4 mm)	TF3DF (6,4 mm)	CE5		
		10	3R10														
		8	3R8														
		6	3R6	356A†	3P13 (13 mm)		3UT	3ULM5 (5 mm)	3ULF5 (5 mm)	3FB14 (14 x 4,5 mm)	3HB3 (3 mm)	3DM	3DF9 (9,4 mm)	F3DMY (6,4 mm Nylon)			
	5	3R5	355														
	4	3R4	354A†														
	3,5	3R35															

NOTE: (1) FOR INNER COPPER TUBE (TWINGRIP) USE PREFIX "T". (2) ‡(A) OPTION NARROWER. (3) SUFFIX "E" AFTER TYPE DENOTES "EASY ENTRY".