

Vinyl Insulated Pin Terminals

Cable size:0.5 ~ 1.5mm²(A.W.G.22 ~ 16) Max current:Imax=19A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:0.75mm

ITEM NO	Dimension(mm)				Color
	F	L	H	Dφ	
PTV 1.25-10	1.9	20.0	10.0	4.3	red
PTV 1.25-12	1.9	22.0			
PTV 1.25-13	1.9	23.0			
PTV 1.25-18	1.9	28.0			

Cable size:1.5 ~ 2.5mm²(A.W.G.22 ~ 16) Max current:Imax=27A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:0.8mm

ITEM NO	Dimension(mm)				Color
	F	L	H	Dφ	
PTV 2-10	1.9	20.0	10.0	4.9	blue
PTV 2-12	1.9	22.0			
PTV 2-13	1.9	23.0			
PTV 2-18	1.9	28.0			

Cable size:2.5 ~ 4mm²(A.W.G.16 ~ 14) Max current:Imax=36A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:1.0mm

ITEM NO	Dimension(mm)				Color
	F	L	H	Dφ	
PTV 3.5-10	2.8	20.0	13.0	6.2	black
PTV 3.5-13	2.8	25.5			

Cable size:4 ~ 6mm²(A.W.G.12 ~ 10) Max current:Imax=48A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:1.0mm

ITEM NO	Dimension(mm)				Color
	F	L	H	Dφ	
PTV 5.5-13	2.8	25.5	13.0	6.7	yellow

