


无绝缘护套套矩形中间平行端子(适用于软线)

- 材质: 紫铜
- 表面处理: 镀锡

Non-Insulated Parallel Terminal  
(Apply in flexible wire)

- Terminal Body: Copper
- Plating: Tin



PVC全绝缘护套套矩形中间平行端子

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡

Vinyl-Insulated Parallel Terminal

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin




#### PARALLEL TERMINAL

型号 Item NO	导线截面Cable Size		最大电流 Max Current	尺寸Dimension(mm)		
	A.W.G	mm <sup>2</sup>		Dφ	dφ	L
PNT 1.25	22-16	0.5-1.5	19A	3.3	2.0	8.0
PNT 2	16-14	1.5-2.5	27A	3.95	2.5	8.0
PNT 5.5	12-10	4-6	48A	5.5	3.9	8.5
PNT 8	#8	6-10	62A	7.0	4.8	9.5
PNT 14	#6	10-16	88A	8.9	5.9	11.0
PNT 22	#4	16-25	115A	11.3	7.8	13.5
PNT 38	#2	35-50	160A	13.2	9.5	16.5
PNT 60	1/0	50-70	215A	15.3	11.4	19.0
PNT 70	2/0	70-95	235A	17.5	13.3	19.0
PNT 80	3/0	95-120	255A	19.5	14.5	19.5
PNT 100	4/0	120-150	300A	22.1	16.4	20.0
PNT 150	(250/300)	150-185	395A	26.0	19.0	27.0
PNT 180	(300/350)	185-240	440A	28.5	21.0	28.5
PNT 200	(400/500)	240-300	470A	32.0	24.0	32.0
PNT 325	(500/600)	300-400	650A	37.0	28.0	37.0

#### PARALLEL TERMINAL

型号 Item NO	导线截面Cable Size		最大电流 Max Current	尺寸Dimension(mm)			颜色 Color
	A.W.G	mm <sup>2</sup>		l	dφ	L	
PVT 1.25	22-16	0.5-1.5	19A	8.0	2.0	16.0	红色 red
PVT 2	16-14	1.5-2.5	27A	8.0	2.5	16.0	蓝色 blue
PVT 5.5	12-10	4-6	48A	8.5	3.9	20.5	黄色 yellow



无绝缘护套中间连接端子(适用于软线)

- 材质: 紫铜
- 表面处理: 镀锡


Non-Insulated Butt Splices Terminal  
(Apply in flexible wire)

- Terminal Body: Copper
- Plating: Tin



### BUTT SPLICE TERMINAL

型号 Item NO	导线截面Cable Size		最大电流 Max Current	尺寸Dimension(mm)		
	A.W.G	mm <sup>2</sup>		Dφ	dφ	L
BN 0.5(G)	26-22	0.2-0.75	9A	2.1	1.4	10.0
BN 1.25(G)	22-16	0.5-1.5	19A	3.3	1.7	15.0
BN 1.25(H)	22-16	0.5-1.5	19A	3.3	2.0	15.0
BN 2(G)	16-14	1.5-2.5	27A	3.95	2.4	15.0
BN 2(H)	16-14	1.5-2.5	27A	3.95	2.5	15.0
BN 3.5(G)	14-12	2.5-4	37A	5.0	3.3	15.0
BN 5.5(G)	12-10	4-6	48A	5.5	3.6	15.0
BN 5.5(H)	12-10	4-6	48A	5.5	3.9	15.0
BN 8(G)	#8	6-10	62A	7.0	4.8	21.0
BN 14(G)	#6	10-16	88A	8.9	5.9	27.0
BN 14(H)	#6	10-16	88A	8.9	6.5	27.0
BN 22(G)	#4	16-25	115A	11.3	7.8	29.0
BN 22(H)	#4	16-25	115A	11.0	8.4	29.0
BN 38(G)	#2	35-50	160A	13.2	9.5	32.0
BN 60(G)	1/0	50-70	215A	15.3	11.4	36.0
BN 70(G)	2/0	70-95	235A	17.5	13.3	37.0
BN 80(G)	3/0	95-120	255A	19.5	14.5	38.0
BN 100(G)	4/0	120-150	300A	22.1	16.4	38.0
BN 150(G)	(250/300)	150-185	395A	26.0	19.0	54.0
BN 180(G)	(300/350)	185-240	440A	28.5	21.0	57.0
BN 200(G)	(400/500)	240-300	470A	32.0	24.0	63.0
BN 325(G)	(500/600)	300-400	650A	37.0	28.0	72.0



PVC全绝缘护套中间连接端子(适用于软线)

- 材质: 紫铜
- 护套: PVC
- 表面处理: 镀锡


Vinyl-Insulated Butt Splices Terminal  
(Apply in flexible wire)

- Terminal Body: Copper
- Insulation: Vinyl
- Plating: Tin



### BUTT SPLICE TERMINAL

型号 Item NO	导线截面Cable Size		最大电流 Max Current	尺寸Dimension(mm)			颜色 Color
	A.W.G	mm <sup>2</sup>		I	dφ	L	
BV 1.25	22-16	0.5-1.5	19A	15.0	2.0	26.0	红色 red
BV 2	16-14	1.5-2.5	27A	15.0	2.5	26.0	蓝色 blue
BV 3.5	14-12	2.5-4	37A	15.0	3.3	26.0	黑色 black
BV 5.5	12-10	4-6	48A	15.0	3.9	26.0	黄色 yellow
BV 8	#8	6-10	62A	21.0	4.8	36.0	红色 red
BV 14	#6	10-16	88A	27.0	5.9	44.0	蓝色 blue
BV 22	#4	16-25	115A	29.0	7.8	50.0	黑色 black
BV 38	#2	35-50	160A	32.0	9.5	55.0	黄色 yellow


**尼龙全绝缘护套中间连接端子(适用于软线)**


- 材质: 紫铜
- 护套: 尼龙
- 温度: 105°C
- 表面处理: 镀锡

**Nylon-Insulated Butt Splices Terminal  
(Apply in flexible wire)**

- Terminal Body: Copper
- Insulation: Nylon
- Temperature: 105°C
- Plating: Tin


**BUTT SPLICE TERMINAL**

型号 Item NO	导线截面Cable Size		最大电流 Max Current	尺寸Dimension(mm)			颜色 Color	
	A.W.G	mm <sup>2</sup>		L	dφ	L		
BNYF 0.5	26-22	0.2-0.75	9A	10.0	2.7	1.4	20.0	黄 yellow
BNYF 1.25	22-16	0.5-1.5	19A	15.0	4.1	2.0	26.5	红 red
BNYF 2	16-14	1.5-2.5	27A	15.0	4.5	2.5	26.5	蓝 blue
BNYF 5.5	12-10	4-6	48A	15.0	6.6	3.9	27.0	黄 yellow

**Heat Shrink Insulated**

**热缩型防水全绝缘护套中间连接端子  
(适用于软线)**

- 材质: 紫铜
- 护套: 耐高温热缩管

**Heat Shrink Insulated  
(Apply in flexible wire)**

- Terminal Body: Copper
- Sheath: Heat Shrink Tube


**BUTT SPLICE TERMINAL**

型号 Item NO	导线截面Cable Size		最大电流 Max Current	尺寸Dimension(mm)			颜色 Color
	A.W.G	mm <sup>2</sup>		L	d1	d2	
BHT 0.5	26-22	0.2-0.75	9A	28.0	3.2	1.4	黄 yellow
BHT 1.25	22-16	0.5-1.5	19A	38.0	4.8	1.7	红 red
BHT 2	16-14	1.5-2.5	27A	38.0	5.8	2.4	蓝 blue
BHT 5.5	12-10	4-6	48A	42.0	6.8	3.6	黄 yellow