



adhesive tapes catalogue

reinforcing tapes



FG 10

Reinforcing and bundling



•••••



Filament tape

Single sided tape, medium resistant, longitudinally reinforced, recommended to secure carton boxes or light steel bundles. High adhesion and resistance to break.

| BACKING | ADHESIVE | COLOUR | TOTAL THICKNESS | ADHESION | TENSILE STRENGTH | ELONGATION TO BREAK | TEMPERATURE RESISTANCE |
|------------|------------------|-------------|-----------------|-----------|------------------|---------------------|------------------------|
| Reinforced | Synthetic rubber | Transparent | 0.110 mm | 21 N/25mm | 700 N/25mm | 6 % | 60 °C |

FG BD

Reinforcing and bundling



•••••



Crossweave reinforced tape

Single sided tape with high resistance to break, recommended to secure heavy packagings.

| BACKING | ADHESIVE | COLOUR | TOTAL THICKNESS | ADHESION | TENSILE STRENGTH | ELONGATION TO BREAK | TEMPERATURE RESISTANCE |
|------------|------------------|-------------|-----------------|-----------|------------------|---------------------|------------------------|
| Reinforced | Synthetic rubber | Transparent | 0.120 mm | 21 N/25mm | 650 N/25mm | 6 % | 60 °C |

PP 550

thermal exchange and white industry



•••••



Holding tape blue

Medium resistant single sided tape, recommended to secure plastic parts inside refrigerators and freezers during manufacturing and transport. No chemical interaction with application surfaces. Removable without residues. Good resistance to break.

| BACKING | ADHESIVE | COLOUR | TOTAL THICKNESS | ADHESION | TENSILE STRENGTH | ELONGATION TO BREAK | TEMPERATURE RESISTANCE |
|------------|----------------|--------|-----------------|------------|------------------|---------------------|------------------------|
| MOPP 55 µm | Natural rubber | Blue | 0.076 mm | 4.3 N/25mm | 350 N/25mm | 33 % | 60 °C |