

PRODUCT
SOLOMON



SOLDERING STATION (11)

- SL-10
- SL-20
- SL-20 ESD
- SL-20CMC
- SL-30
- SL-30 ESD
- SL-30CMC
- SL-30CMCESD
- SR-976
- SR-976ESD
- SR-998

DESOLDERING STATION (3)

SUCKER TIN PUMP (4)

HOT AIR SMD REWORK STATION (1)

SOLDERING IRON (22)

SOLDERING IRON STAND (3)

STAINLESS TWEEZERS (3)

RHINESTONE APPLICATOR (1)

SPECIAL SOLDERING TIP (1)

PRODUCT LINE

PRODUCT LINE > SOLDERING STATION(11) > SL-20

SL-20



SPECIFICATIONS



Voltage	110/120V AC or 220/240 V AC	
Power consumption	48W	
Temp.setting range	150°C~420°C 300°F~790°F	
Heater Operating Voltage	24V AC	
Size	Handpiece	203mm
	Station	L170:W116:H96 (mm)
Weight	1900g	
Station-Handpiece cordlength	115 cm	
AC Power cord	2pin or 3pin plug 180cm	
Packing Measure	8 pcs CUFT 1.77'	

DESCRIPTION

ADJUSTABLE TEMPERATURE CONTROLLED SOLDERING STATION

There are 12 LED displays on the panel of the SL-20 temperature-control soldering iron station thus making the temperature adjustment ranging from 150C to 420C, such an adjustment range is very suitable for the engineers to perform maintenance work, factory soldering and welding work and is also good for doing household works.

CHARACTER



EUROPE STANDARD



AMERICA STANDARD



Copyright 2007 Somy Roong Industrial Co.,Ltd. ALL RIGHTS RESERVED.
 Address:4F.No.138.Chung Cheng Rd.,Chung Ho City,Taipei Hsien, Taiwan R.O.C.
 TEL:886-2-2244-6128 / FAX:886-2-2244-6803
 E-mail:solomon@soldering.com.tw / somyroong@soldering.com.tw