



## MATERIAL FACT SHEET

### 298614 TH-T100KP 67A

#### General Data

Product Hierarchy	IAN50305
	MC
	TH-T Body
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000298614](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000298614)

#### FA-MC: Overload Protection Relays

Series	MS-T THERMAL OVERLOAD RELAY
Type	WITH 3-ELEMENT (2E)
Heater Designation (A)	67
Range of Setting Current (A)	54 - 80
Rated Capacity (kW)	3-PHASE 220-240V: 18.5, 19
Rated Capacity (kW) (2)	3-PHASE 380-440V: 37
Rated Voltage (V)	690
Frequency Range (Hz)	0(DC) - 400
Min. Ambient Temperature (°C)	-10
Max. Ambient Temperature (°C)	+40
No of Auxiliary Contacts NO	1
No of Auxiliary Contacts NC	1

#### Product Dimensions & Weight

Width (mm)	89
Height (mm)	73,5
Depth (mm)	83,5
Weight (kg)	0,32

#### Logistic Dimensions & Gross Weight

Length (cm)	9,0
Width (cm)	7,5
Height (cm)	8,5
Gross Weight (kg)	0,404
Volume (cdm)	0,574

#### Stock Data

Planned Delivery Time (Days)	194
------------------------------	-----

#### Life Cycle

Sales Start	01.11.2016
Predecessor	113715 / TH-N60TAKP 67A

#### Additional Product Information

Battery included	NO
------------------	----

#### Export Data

Commodity Code	85363030
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO

RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=TH-T100KP%2067A&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=TH-T100KP%2067A&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=TH-T100KP%2067A&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=TH-T100KP%2067A&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=TH-T100KP%2067A&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=TH-T100KP%2067A&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	200
Other paper (g)	10
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0