



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max.

■ HOUSING

- Part No. : JS-2001-XX
JS-2001-XX : GP Produces
- Poles : 2 - 20
- Material : Base : Nylon 66 UL94V-0
- Q' ty : 1000 pcs./Bag

Poles	Part No.	Dimensions (mm)		
		A	B	C
2	JS-2001-02	2.50	5.70	7.30
3	JS-2001-03	5.00	8.20	9.80
4	JS-2001-04	7.50	10.70	12.30
5	JS-2001-05	10.00	13.20	14.80
6	JS-2001-06	12.50	15.70	17.30
7	JS-2001-07	15.00	18.20	19.80
8	JS-2001-08	17.50	20.70	22.30
9	JS-2001-09	20.00	23.20	24.80
10	JS-2001-10	22.50	25.70	27.30
11	JS-2001-11	25.00	28.20	29.80
12	JS-2001-12	27.50	30.70	32.30
13	JS-2001-13	30.00	33.20	34.80
14	JS-2001-14	32.50	35.70	37.30
15	JS-2001-15	35.00	38.20	39.80
16	JS-2001-16	37.50	40.70	42.30
17	JS-2001-17	40.00	43.20	44.80
18	JS-2001-18	42.50	45.70	47.30
19	JS-2001-19	45.00	48.20	49.80
20	JS-2001-20	47.50	50.70	52.30

SHALLIN ELECTRONICS CO., LTD	APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
		3:1	mm	.0 ±0.3 .00 ±0.2	ECR	RoHS Compliant	06/04/01			
PART NO YY05CXX	CHECKED BY	PROJ	VER NO.	.000 ±0.1 ALL ±						
	DRAWN BY	DATE	SIZE	ANGLE						
2.50mm crimp style connectors Housing		2005/05/15	A4	0° ± .0° ±					Conforms to The RoHS Instruction	