

SELECTION TABLE

Model	Step Angle (°)	Motor Length L(mm)	Rate Voltage (V)	Rate Current (A)	Phase Resistance (Ω)	Phase Inductance (mH)	Holding Torque (kg.cm)	Lead Wire (NO.)	Rotor Inertia (g.cm ²)	Detent Torque (N.cm)	Motor Weight (kg)
85BYGH450A-040	1.8	80	1.6	4	0.41	2.5	40	4	1400	6.5	3
85BYGH450A-002	1.8	80	2.8	4	0.7	3	30	8	1400	6.5	3
85BYGH450D-002	1.8	100	3.2	4	0.8	3.5	49	8	1700	9.5	3.5
85BYGH450D-007	1.8	100	6.4	2	3.2	15	45	8	1700	9.5	3.5
85BYGH450D-008	1.8	100	2.13	5.6	0.38	4.1	77	4	1700	9.5	3.5
85BYGH450B-004	1.8	116	1.9	3.5	0.53	6.5	84	4	2700	12.5	3.8
85BYGH450B-056	1.8	116	3.08	5.6	0.55	5.5	84	4	2900	12.5	3.8
85BYGH450C-012	1.8	151	5.6	3.5	1.6	22	115	4	3600	24.5	5.5
85BYGH450C-060	1.8	151	3.6	6	0.6	8	120	4	4000	24.5	5.5
85BYGH450A-040-35	1.8	66	1.68	4.0	0.42	2.3	32	4	1000	5.5	3
85BYGH450E-060-120	1.8	126	2.58	6.0	0.43	5.5	105	4	2900	12.5	3.8