

### 730 GDA

Flooring and carpet



#### High adhesion, all purpose tape

High performance double sided cloth carpet tape. Very high adhesion to secure fixing on difficult substrates. High tack and adhesion. High conformability. Easy to tear by hand.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Synthetic cloth	Synthetic rubber	White (brown paper liner)	0.235 mm	Ext: 30 N/25mm Int: 25 N/25mm	80 N/25mm	15 %	60 °C

### 756 TRANSFER

Fixing, mounting and fastening



#### Multipurpose, versatile

Film of adhesive without backing, general purpose, to fix various items in the industry, craft industry, at school and at home. Good adhesion on all substrates (cardboard, paper, leather, fabrics, plastics, wood). Good ageing resistance. Temperature resistance up to 80°C (up to 130°C short period).

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Without backing	Acrylic solvent based	Transparent (brown paper liner)	0.050 mm	Ext: 9.5 N/25mm Int: 9.5 N/25mm	\	\	80 °C

### 770 PROFIL

Car refinishing and repairing



#### Long term foam

Double sided black foam tape to mount plates, emblems and profiles in the automotive sector. High adhesion. Excellent resistance to UV, weather conditions and ageing. High elongation and conformability.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Foam 0.8 mm	Acrylic solvent based	Black (green LDPE liner)	0.850 mm	Ext: 14 N/25mm Int: 14 N/25mm	24 N/25mm	220 %	90 °C

### DS FOAM 1.5

Fixing, mounting and fastening



#### 1.5 foam, medium adhesion

Double sided foam tape suitable for wall hooks. Excellent adhesion and holding power. High bond, weatherproof and solvent resistant.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Foam	Acrylic adhesive	White (white paper liner)	1.500 mm	> 19.6 N/25mm	\	\	60 °C